
Product family datasheet

DECOSTAR 51 ALU

Halogen alu coated glas reflector lamps with 51 mm diameter

- General illumination Shops Restaurants, hotels and similar prestigious applications Offices, public buildings



- Brilliant accent light No light can escape at the back of the reflector Approved for use in open luminaires (to IEC 60598-1) UV filter Aluminum-coated reflector without a shield reduces thermal load in luminaire Reduced thermal load: ~60 % compared with aluminum-coated reflectors with shield Reduced thermal load: ~80 % compared with dichroic reflectors with shield

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

References / Links

For light distribution curves see

▶ www.osram.com

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany