

Product family datasheet

OSRAM DULUX T/E PLUS

CFLni, 3 tubes, with 4-pin base for ECG operation




Product family datasheet

| Technical data | | | | | | | |
|---------------------------------------|--------------------|--|----------------------------|----------------------------------|-------------------------------------|-------------------------|--------------------------|
| | Electrical data | Photometrical data | Dimensions & weight | | Temperatures & operating conditions | Additional product data | Certificates & standards |
| Product description | Nominal current | Light color (designation) | Overall length | Product weight | Ambient temperature range | Product remark | Energy efficiency class |
| DULUX T/E PLUS 18 W/840 ¹⁾ | 0.23 A A | LUMILUX Cool White | 117.00 mm | 56.00 g | -5...+40 °C | For ECG operation only | G |
| DULUX T/E PLUS 26 W/830 ¹⁾ | 0.33 A A | LUMILUX Warm White | 131.50 mm | 62.5 g | -5...+40 °C | For ECG operation only | G |
| DULUX T/E PLUS 26 W/840 ¹⁾ | 0.33 A A | LUMILUX Cool White | 131.50 mm | 62.5 g | -5...+40 °C | For ECG operation only | G |
| DULUX T/E PLUS 32 W/830 ¹⁾ | 0.32 A A | LUMILUX Warm White | 148.00 mm | 69.5 g | -5...+40 °C | For ECG operation only | G |
| DULUX T/E PLUS 32 W/840 ¹⁾ | 0.32 A A | LUMILUX Cool White | 148.00 mm | 69.5 g | -5...+40 °C | For ECG operation only | G |
| DULUX T/E PLUS 42 W/830 ¹⁾ | 0.32 A A | LUMILUX Warm White | 169.00 mm | 80.00 g | -5...+40 °C | For ECG operation only | G |
| DULUX T/E PLUS 42 W/840 ¹⁾ | 0.32 A A | LUMILUX Cool White | 169.00 mm | 80.00 g | -5...+40 °C | For ECG operation only | G |
| | | Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) | | | | | |
| Product description | Energy consumption | Date of Declaration | Primary Article Identifier | Declaration No. in SCIP database | | | |
| DULUX T/E PLUS 18 W/840 ¹⁾ | 19.00 kWh/1000h | 18-04-2022 | 4050300342221 | In work | | | |
| DULUX T/E PLUS 26 W/830 ¹⁾ | 28.00 kWh/1000h | 18-04-2022 | 4050300342306 | In work | | | |
| DULUX T/E PLUS 26 W/840 ¹⁾ | 28.00 kWh/1000h | 18-04-2022 | 4050300342283 | In work | | | |
| DULUX T/E PLUS 32 W/830 ¹⁾ | 32.00 kWh/1000h | 18-04-2022 | 4050300348582 | In work | | | |
| DULUX T/E PLUS 32 W/840 ¹⁾ | 32.00 kWh/1000h | 18-04-2022 | 4050300348568 | In work | | | |

| | | Environmental information | | |
|---------------------------------------|--------------------|---|----------------------------|----------------------------------|
| | | Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) | | |
| Product description | Energy consumption | Date of Declaration | Primary Article Identifier | Declaration No. in SCIP database |
| DULUX T/E PLUS 42 W/830 ¹⁾ | 44.00 kWh/1000h | 18-04-2022 | 4050300425641 | In work |
| DULUX T/E PLUS 42 W/840 ¹⁾ | 44.00 kWh/1000h | 18-04-2022 | 4050300425627 | In work |

¹⁾ For ECG operation only



DULUX T/E PLUS 18 W/840, DULUX T/E PLUS 26 W/830, DULUX T/E PLUS 26 W/840

DULUX T/E PLUS 32 W/830, DULUX T/E PLUS 32 W/840, DULUX T/E PLUS 42 W/830, DULUX T/E PLUS 42 W/840

DULUX T/E PLUS 18 W/840, DULUX T/E PLUS 26 W/840, DULUX T/E PLUS 32 W/840, DULUX T/E PLUS 42 W/840

DULUX T/E PLUS 26 W/830, DULUX T/E PLUS 32 W/830, DULUX T/E PLUS 42 W/830

Product family datasheet

Equipment / Accessories

- Suitable for operation on electronic control gear

Application advice

For more detailed application information and graphics please see product datasheet.

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|-------------------------|------------------------------|--------------------------------------|----------------------|--------------|
| 4050300342221 | DULUX T/E PLUS 18 W/840 | Shipping carton box 10 | 240 mm x 102 mm x 146 mm | 3.57 dm ³ | 732.00 g |
| 4050300342306 | DULUX T/E PLUS 26 W/830 | Shipping carton box 10 | 260 mm x 105 mm x 159 mm | 4.34 dm ³ | 1117.00 g |
| 4050300342283 | DULUX T/E PLUS 26 W/840 | Shipping carton box 10 | 260 mm x 159 mm x 116 mm | 4.80 dm ³ | 853.00 g |
| 4050300348582 | DULUX T/E PLUS 32 W/830 | Shipping carton box 10 | 227 mm x 153 mm x 148 mm | 5.14 dm ³ | 901.00 g |
| 4050300348568 | DULUX T/E PLUS 32 W/840 | Shipping carton box 10 | 240 mm x 172 mm x 125 mm | 5.16 dm ³ | 911.00 g |

Product family datasheet

Logistical Data

| | | | | | |
|---------------|-------------------------|---------------------------|--------------------------|----------------------|-----------|
| 4050300425641 | DULUX T/E PLUS 42 W/830 | Shipping carton box 10 | 260 mm x 105 mm x 190 mm | 5.19 dm ³ | 1381.00 g |
| 4050300425627 | DULUX T/E PLUS 42 W/840 | Shipping carton box 10 | 256 mm x 101 mm x 187 mm | 4.84 dm ³ | 1009.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For more information on QUICKTRONIC electronic control gear go to
▶ www.osram.com/QUICKTRONIC

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany