

Product family datasheet

OSRAM DULUX D

CFLni, 2 tubes, with 2-pin base for CCG operation



Product family datasheet




Technical data

Product description	Electrical data	Photometrical data	Dimensions & weight		Temperatures & operating conditions	Certificates & standards	
	Nominal current	Light color (designation)	Overall length	Product weight	Ambient temperature range	Energy efficiency class	Energy consumption
DULUX D 13 W/840	0.18 A A	LUMILUX Cool White	138.00 mm	37.5 g	-5...+40 °C	G	14.00 kWh/1000h
DULUX D 18 W/830 ¹⁾	0.22 A A	LUMILUX Warm White	153.00 mm	39.00 g	-5...+40 °C	G	19.00 kWh/1000h
DULUX D 18 W/840 ¹⁾	0.22 A A	LUMILUX Cool White	153.00 mm	39.00 g	-5...+40 °C	G	19.00 kWh/1000h
DULUX D 26 W/830	0.33 A A	LUMILUX Warm White	172.00 mm	43.00 g	-5...+40 °C	G	27.00 kWh/1000h
DULUX D 26 W/840	0.33 A A	LUMILUX Cool White	172.00 mm	43.00 g	-5...+40 °C	G	27.00 kWh/1000h

Product description	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)			Additional product data
	Date of Declaration	Primary Article Identifier	Declaration No. in SCIP database	Product remark
DULUX D 13 W/840	18-04-2022	4050300010625	In work	
DULUX D 18 W/830 ¹⁾	18-04-2022	4050300025704	In work	Suitable only for operation with 0.22 A control gear
DULUX D 18 W/840 ¹⁾	18-04-2022	4050300012056	In work	Suitable only for operation with 0.22 A control gear
DULUX D 26 W/830	18-04-2022	4050300025711	In work	
DULUX D 26 W/840	18-04-2022	4050300012049	In work	

¹⁾ Suitable only for operation with 0.22 A control gear

Product family datasheet



DULUX D 13 W/840, DULUX D 18 W/830, DULUX D 18 W/840, DULUX D 26 W/830, DULUX D 26 W/840

DULUX D 13 W/840, DULUX D 18 W/840, DULUX D 26 W/840

DULUX D 18 W/830, DULUX D 26 W/830

Equipment / Accessories

– Suitable for operation on conventional control gear

Application advice

For more detailed application information and graphics please see product datasheet.

Product family datasheet

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300010625	DULUX D 13 W/840	Shipping carton box 10	187 mm x 161 mm x 84 mm	2.53 dm ³	583.00 g
4050300025704	DULUX D 18 W/830	Shipping carton box 10	153 mm x 174 mm x 119 mm	3.17 dm ³	645.00 g
4050300012056	DULUX D 18 W/840	Shipping carton box 10	186 mm x 163 mm x 110 mm	3.33 dm ³	609.00 g
4050300025711	DULUX D 26 W/830	Shipping carton box 10	135 mm x 162 mm x 167 mm	3.65 dm ³	695.00 g
4050300012049	DULUX D 26 W/840	Shipping carton box 10	157 mm x 188 mm x 120 mm	3.54 dm ³	705.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany