

Product family datasheet

OSRAM DULUX S

Short CFLni, with 2-pin base for CCG operation



Product family datasheet

Technical data

	Electrical data	Photometrical data	Dimensions & weight		Temperatures & operating conditions	Certificates & standards	
Product description	Nominal current	Light color (designation)	Overall length	Product weight	Ambient temperature range	Energy efficiency class	Energy consumption
DULUX S 9 W/827	0.17 A A	LUMILUX INTERNA	166.50 mm	24.1 g	-5...+40 °C	G	10.00 kWh/1000h
DULUX S 9 W/830	0.17 A A	LUMILUX Warm White	166.50 mm	24.1 g	-5...+40 °C	G	10.00 kWh/1000h
DULUX S 9 W/840	0.17 A A	LUMILUX Cool White	166.50 mm	24.1 g	-5...+40 °C	G	10.00 kWh/1000h
DULUX S 11 W/830	0.16 A A	LUMILUX Warm White	236.50 mm	30.7 g	-5...+40 °C	G	13.00 kWh/1000h
DULUX S 11 W/840	0.16 A A	LUMILUX Cool White	236.50 mm	30.7 g	-5...+40 °C	G	13.00 kWh/1000h

	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
Product description	Date of Declaration	Primary Article Identifier	Declaration No. in SCIP database
DULUX S 9 W/827	18-04-2022	4050300006000	In work
DULUX S 9 W/830	18-04-2022	4050300025742	In work
DULUX S 9 W/840	18-04-2022	4050300010588	In work
DULUX S 11 W/830	18-04-2022	4050300025759	In work
DULUX S 11 W/840	18-04-2022	4050300010618	In work

—	DULUX S 9 W/827, DULUX S 9 W/830, DULUX S 9 W/840, DULUX S 11 W/830, DULUX S 11 W/840	DULUX S 9 W/827	DULUX S 9 W/830, DULUX S 11 W/830	DULUX S 9 W/840, DULUX S 11 W/840
---	---	-----------------	-----------------------------------	-----------------------------------

Equipment / Accessories

- Suitable for operation on conventional control gear

Application advice

For more detailed application information and graphics please see product datasheet.

Product family datasheet

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300006000	DULUX S 9 W/827	Shipping carton box 10	126 mm x 81 mm x 183 mm	1.87 dm ³	393.00 g
4050300025742	DULUX S 9 W/830	Shipping carton box 10	126 mm x 81 mm x 183 mm	1.87 dm ³	420.00 g
4050300010588	DULUX S 9 W/840	Shipping carton box 10	126 mm x 81 mm x 183 mm	1.87 dm ³	560.00 g
4050300025759	DULUX S 11 W/830	Shipping carton box 10	126 mm x 81 mm x 251 mm	2.56 dm ³	580.00 g
4050300010618	DULUX S 11 W/840	Shipping carton box 10	126 mm x 81 mm x 251 mm	2.56 dm ³	545.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany