

Product family datasheet

OSRAM DULUX S/E

Short CFLni, with 4-pin base for ECG operation



– Offices, public buildings Shops Supermarkets and department stores Hotels, restaurants

– Extremely economical Good quality of light Improved maintenance Low power consumption (7 W, 9 W, 11 W) Long service life Extremely low profile



Product family datasheet



Technical data

	Electrical data	Photometrical data	Dimensions & weight		Temperatures & operating conditions	Additional product data	Certificates & standards
Product description	Nominal current	Light color (designation)	Overall length	Product weight	Ambient temperature range	Product remark	Energy efficiency class
DULUX S/E 9 W/840 ¹⁾	0.17 A A	LUMILUX Cool White	151.80 mm	21.9 g	-5...+40 °C	For ECG operation only	G
DULUX S/E 11 W/840 ¹⁾	0.16 A A	LUMILUX Cool White	221.80 mm	29.5 g		For ECG operation only	G

		Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
Product description	Energy consumption	Date of Declaration	Primary Article Identifier	Declaration No. in SCIP database
DULUX S/E 9 W/840 ¹⁾	9.00 kWh/1000h	18-04-2022	4050300020174	In work
DULUX S/E 11 W/840 ¹⁾	13.00 kWh/1000h	18-04-2022	4050300020181	In work

¹⁾ For ECG operation only

Product family datasheet



DULUX S/E 9 W/840, DULUX S/E 11
W/840

DULUX S/E 9 W/840, DULUX S/E 11
W/840

Equipment / Accessories

- Suitable for operation on electronic control gear

Application advice

For more detailed application information and graphics please see product datasheet.

Product family datasheet

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300020174	DULUX S/E 9 W/840	Shipping carton box 10	143 mm x 136 mm x 105 mm	2.04 dm ³	378.00 g
4050300020181	DULUX S/E 11 W/840	Shipping carton box 10	224 mm x 138 mm x 97 mm	3.00 dm ³	513.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For more information on QUICKTRONIC electronic control gear go to

▶ www.osram.com/QUICKTRONIC

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany