

Product datasheet

DULUX S/E 9 W/840

OSRAM DULUX S/E | Short CFLni, with 4-pin base for ECG operation

- Offices, public buildings Shops Supermarkets and department stores Hotels, restaurants



- Extremely economical Good quality of light Improved maintenance Low power consumption (7 W, 9 W, 11 W) Long service life Extremely low profile



Product datasheet

Technical data


Electrical data

Nominal current	0.17 A A
-----------------	----------

Photometrical data

Light color (designation)	LUMILUX Cool White
Luminous flux	600 lm
Color rendering index Ra	≥80

Dimensions & weight



Overall length	151.80 mm
Length with base excl. base pins/connection	145 mm
Product weight	21.9 g

Temperatures & operating conditions

Ambient temperature range	-5...+40 °C
---------------------------	-------------

Lifespan

Service life	13000 h
Nominal lamp life time	12000 h

Additional product data

Mercury content	1.6 mg
Appropriate disposal acc. to WEEE	Yes
Product remark	For ECG operation only

Certificates & standards

Energy efficiency class	G
-------------------------	---

Product datasheet

Energy consumption	9.00 kWh/1000h
--------------------	----------------


Country specific categorizations

ILCOS	FSDH-9/840-/P/-2G7
-------	--------------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-04-2022
Primary Article Identifier	4050300020174
Declaration No. in SCIP database	In work

Light Distribution




FL_840


Equipment / Accessories

- Suitable for operation on electronic control gear


Product datasheet



SINGLE LAMP WITH ACCUTRONIC AT



SERIES CONNECTION WITH QUICKTRONIC QT-DE



SINGLE LAMP WITH QUICKTRONIC QT-DE

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300020174	DULUX S/E 9 W/840	Shipping carton box 10 Pieces Folding carton box	143 mm x 136 mm x 105 mm	2.04 dm ³	378.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Product datasheet

References / Links

For more information on QUICKTRONIC electronic control gear go to

▶ www.osram.com/QUICKTRONIC

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany

DULUX S/E 9 W/840

OSRAM DULUX S/E | Short CFLni, with 4-pin base for ECG operation

Product name	Product name ECG	EAN	Nominal current	Nominal wattage + Power loss	Power factor λ [PIM]	Luminous flux at 25 °C
DULUX S/E 9 W/840	QT-ECO 1x4-16/220-240 S	4050300638584	0.07 A	10.00 W	0.60 c	600 lm
	QT-ECO 2x5-11/220-240 S	4050300821504	0.13 A	18.00 W	0.60 c	550 lm
	QTP-D/E 1x10-13	4008321181572	0.05 A	9.50 W	0.92 c	600 lm
	QTP-D/E 2x10-13	4008321181596	0.09 A	18.00 W	0.92 c	600 lm

Product name	Product name ECG	EAN	Number of lighting outlets	EEI – Energy Label
DULUX S/E 9 W/840	QT-ECO 1x4-16/220-240 S	4050300638584	1	A3
	QT-ECO 2x5-11/220-240 S	4050300821504	2	A2 BAT
	QTP-D/E 1x10-13	4008321181572	1	
	QTP-D/E 2x10-13	4008321181596	2	