

Product datasheet

DULUX L 55 W/954 2G11

OSRAM DULUX L LUMILUX DE LUXE | CFLni, with 4-pin 2G11 base for ECG/CCG operation, high color rendering



Product datasheet

Technical data


Electrical data

Nominal current	0.55 A A
-----------------	----------

Photometrical data

Light color (designation)	LUMILUX DE LUXE Daylight
Rated LLMF at 4,000 h	0.77
Rated LLMF at 6,000 h	0.75
Rated LLMF at 8,000 h	0.73
Rated LLMF at 12,000 h	0.71
Rated LLMF at 16,000 h	0.7
Rated LLMF at 20,000 h	0.68
Luminous flux	3600 lm
Color rendering index Ra	≥90

Dimensions & weight



Overall length	538.00 mm
Tube diameter	17,5 mm
Length with base excl. base pins/connection	532 mm
Product weight	120.5 g

Temperatures & operating conditions

Ambient temperature range	-5...+40 °C
---------------------------	-------------

Lifespan

Service life	13000 h
Nominal lamp life time	20000 h

Product datasheet

Additional product data

Mercury content	5.0 mg
Appropriate disposal acc. to WEEE	Yes
Product remark	For ECG operation only

Certificates & standards

Energy efficiency class	G
Energy consumption	58.00 kWh/1000h

Country specific categorizations


ILCOS	FSDH-55/954-/P/-2G11-43,9/533
-------	-------------------------------

Environmental information


Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-04-2022
Primary Article Identifier	4050300321400
Declaration No. in SCIP database	In work

Equipment / Accessories

- Suitable for operation on electronic and conventional control gear



SERIES CONNECTION WITH QUICKTRONIC



SINGLE LAMP WITH QUICKTRONIC

Product datasheet

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300321400	DULUX L 55 W/954 2G11	Shipping carton box 10 Pieces Folding carton box	136 mm x 103 mm x 578 mm	8.10 dm ³	1663.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For more information on QUICKTRONIC electronic control gear go to
▶ www.osram.com/QUICKTRONIC

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany