

# Product family datasheet

## Basic T5 Short

Tubular fluorescent lamps 16 mm, short, with G5 base




Product family datasheet

Technical data

	Electrical data	Photometrical data	Dimensions & weight			Certificates & standards	
Product description	Nominal current	Light color (designation)	Tube diameter	Overall length	Product weight	Energy consumption	Energy efficiency class
L 6 W/640	0.16 A A	Cool White	16 mm	226.30 mm	20.02 g	7.00 kWh/1000h	G
L 8 W/640	0.15 A A	Cool White	16 mm	302.50 mm	25.71 g	8.00 kWh/1000h	G
L 13 W/640	0.17 A A	Cool White	16 mm	531.10 mm	42.65 g	14.00 kWh/1000h	G

	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
Product description	Date of Declaration	Primary Article Identifier	Declaration No. in SCIP database
L 6 W/640	18-04-2022	4050300008899	In work
L 8 W/640	18-04-2022	4050300008912	In work
L 13 W/640	18-04-2022	4050300008974	In work

## Product family datasheet



L 6 W/640, L 8 W/640, L 13 W/640

L 6 W/640, L 8 W/640, L 13 W/640

---

### System guarantee

OSRAM System+ Guarantee in combination with OSRAM ECGs

---

### Application advice

For more detailed application information and graphics please see product datasheet.

Product family datasheet

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300008899	L 6 W/640	Shipping carton box 25	247 mm x 103 mm x 109 mm	2.77 dm <sup>3</sup>	713.00 g
4050300008912	L 8 W/640	Shipping carton box 25	316 mm x 103 mm x 109 mm	3.55 dm <sup>3</sup>	929.00 g
4050300008974	L 13 W/640	Shipping carton box 25	545 mm x 103 mm x 109 mm	6.12 dm <sup>3</sup>	1176.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For more information on QUICKTRONIC electronic control gear go to  
▶ [www.osram.com/QUICKTRONIC](http://www.osram.com/QUICKTRONIC)

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner  
of LEDVANCE of LAMPS

**OSRAM**

OSRAM GmbH  
Marcel-Breuer-Strasse 6  
80807 Munich, Germany