

# Product datasheet

## L 36 W/950

COLOR proof T8 | Tubular fluorescent lamps 26 mm, with G13 bases, color-proof



- Printing industry, graphic workshops, photographic laboratories Industrial inspection and color matching facilities Industry Shops Incoming goods inspection

- Outstanding OSRAM quality Accurate chromaticity coordinates Stable light-technical and electrical data Uniform coating



Technical data

Electrical data

Nominal current	0.43 A A
-----------------	----------

Photometrical data

Light color (designation)	Daylight
Rated LLMF at 2,000 h	0.9
Rated LLMF at 4,000 h	0.86
Rated LLMF at 6,000 h	0.84
Rated LLMF at 8,000 h	0.81
Rated LLMF at 12,000 h	0.79
Rated LLMF at 16,000 h	0.78
Luminous flux	2150 lm

Dimensions & weight



Tube diameter	26 mm
Length with base excl. base pins/connection	1200 mm
Product weight	165.00 g
Overall length	1213.60 mm

Lifespan

Service life	2500 h
--------------	--------

Additional product data

Mercury content	5.3 mg
Appropriate disposal acc. to WEEE	Yes

Certificates & standards

Product datasheet

Energy efficiency class	G
Energy consumption	38.00 kWh/1000h

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	19-01-2022
Primary Article Identifier	4008321423047
Declaration No. in SCIP database	In work

Light Distribution

---

FL\_950\_ColorProof

DUO CIRCUIT

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321423047	L 36 W/950	Shipping carton box 10 Pieces Sleeves	1256 mm x 151 mm x 74 mm	14.03 dm <sup>3</sup>	2313.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For more information on QUICKTRONIC electronic control gear go to  
▶ [www.osram.com/QUICKTRONIC](http://www.osram.com/QUICKTRONIC)

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner  
of LEDVANCE of LAMPS

**OSRAM**

OSRAM GmbH  
Marcel-Breuer-Strasse 6  
80807 Munich, Germany