

Product datasheet L 22 W/827 G10Q

LUMILUX T9 C | Circular fluorescent lamps 29 mm, with G10Q base







Product datasheet

Technical data

Electrical data

Photometrical data

Light color (designation)	LUMILUX INTERNA		
Rated LLMF at 2,000 h	0.8		
Rated LLMF at 4,000 h	0.74		
Rated LLMF at 6,000 h	0.72		
Rated LLMF at 8,000 h	0.7		
Luminous flux	1250 lm		

Dimensions & weight

Product datasheet

Tube diameter	29 mm
Product weight	124.4 g
Overall length	209.00 mm

Lifespan

Service life	6300 h
--------------	--------

Additional product data

Mercury content	4.8 mg		
Appropriate disposal acc. to WEEE	Yes		

Certificates & standards

Energy efficiency class	G		
Energy consumption	23.00 kWh/1000h		

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Date of Declaration	18-04-2022		
Primary Article Identifier	4008321581068		
Declaration No. in SCIP database	In work		

Product datasheet
Light Distribution
FL_827
Equipment / Accessories
- Suitable for operation on electronic and conventional control gears
DUO CIRCUIT

Product datasheet

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321581068	L 22 W/827 G10Q	Shipping carton box 12 Pieces Sleeves	450 mm x 238 mm x 227 mm	24.31 dm³	2547.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For more information on QUICKTRONIC electronic control gear go to

www.osram.com/QUICKTRONIC

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner of LEDVANCE of LAMPS



OSRAM GmbH Marcel-Breuer-Strasse 6 80807 Munich, Germany

L 22 W/827 G10Q

LUMILUX T9 C | Circular fluorescent lamps 29 mm, with G10Q base

Product name	Product name ECG	EAN	Nominal current	Nominal wattage + Power loss	Power factor λ [PIM]	Luminous flux at 35 °C
L 22 W/827 G10Q	QT-ECO 1x18-24/220-240 S	4050300638560	0.14 A	20.00 W	0.60 c	1250 lm
Product name	Product name ECG	EAN	Number of l outlets	ighting		
L 22 W/827 G100	OT-ECO 1x18-24/220-240 S	4050300638560	1			