


QTi DALI 1X14/24 DIM

QUICKTRONIC INTELLIGENT DALI DIM T5 | ECG dimmable DALI for FL 16 mm



Product family features

- Corridor function for direct connection of ECG to common motion sensor
- Corridor function with pre-programmed light program
- Touch DIM function for free parameterization of light value and turn on time
- Fit for SMART GRID for feedback of consumed mains power and lamp operating hours
- Fit for emergency function for automatic detection of emergency lighting by ECG
- Very low standby power consumption: < 0.5 W
- Lifetime: > 100,000 h (for T = 65 °C at T_c)
- Very high number of switching cycles: up to 300,000
- Dimming range: 1...100 % (3...100 % with compact fluorescent lamp)
- POWER2LAMP function for optimal matching of ECG power to lamp during lamp lifetime
- Line frequency: 0 Hz, 50...60 Hz, rectified AC

Product family benefits

- System+ Guarantee available
- Easy integration in luminaire thanks to same dimensions like DALI GI ECG
- TouchDIM function for easy and inexpensive dimming of several ECGs
- Same luminous flux with direct and alternating current
- Dimming of amalgam lamps without flickering or reduced lifespan
- Automatic restart after lamp replacement

DALI product features

- Control via the DALI interface
- Compliance with the DALI Version-1 and IEC 60929
- Control input protected against overvoltage and polarity reversal (OSRAM ECG)

Touch DIM and Touch DIM Sensor function

- Manual dimming without controller and with standard switches
- Including memory function (double click) and soft start

Product datasheet

Areas of application

- Suitable for use in emergency lighting systems as per EN 50172/DIN VDE 0108-100
- Installation in emergency lighting systems according to IEC 61347-2-3, appendix J
- Industry
- Open-plan offices, corridors and storage rooms
- Public buildings
- Sports halls and factories
- Strip lighting
- Shop lighting
- Suitable for luminaires of protection class I

Product datasheet

Technical data

Electrical data

| | |
|--|-----------------------|
| Input voltage AC | 198...264 V |
| Nominal voltage | 220...240 V |
| Mains frequency | 50...60 Hz |
| Input voltage DC | 154...276 V |
| Maximum output power | 24 W |
| Efficiency in full-load | 89 % ¹⁾ |
| Networked standby power | <0.25 W ¹⁾ |
| Operating frequency | 53...120 kHz |
| Max. ECG no. on circuit breaker 10 A (B) | 17 ²⁾ |
| Max. ECG no. on circuit breaker 16 A (B) | 28 ²⁾ |
| Inrush current | 24 A |

¹⁾ at 230 V, 50 Hz


²⁾ Type B

Light technical data

| | |
|---------------|---------------------|
| Starting time | 0.6 s ¹⁾ |
|---------------|---------------------|

¹⁾ Optimized preheat start

Dimensions & weight



| | |
|----------------------------------|---|
| Length | 360.0 mm |
| Width | 30.0 mm |
| Height | 21.0 mm |
| Mounting hole spacing, length | 350.0 mm |
| Product weight | 278.00 g |
| Cable cross-section, output side | 0.5...1.5 / 0.5...1.0 mm ² ¹⁾ |
| Cable cross-section, input side | 0.5...1.5 / 0.5...1.0 mm ² ¹⁾ |

¹⁾ Solid leads / Flexible

Temperatures & operating conditions

| | |
|---|------------------------|
| Ambient temperature range | +10...+50 °C |
| Permitted rel. humidity during operation | 5...85 % ¹⁾ |

¹⁾ Maximum 56 days/year at 85 %

Lifespan

| | |
|---------------------|------------------------|
| ECG lifetime | 100000 h ¹⁾ |
|---------------------|------------------------|

¹⁾ At $T_{case} = 65^{\circ}C$ at T_c point / 10% failure rate

Expected Lifetime

| Product name | Lamp group | | | | |
|----------------------|--------------|------------------------------|--------|--------|--------|
| QTi DALI 1X14/24 DIM | DULUX L 24 W | ECG ambient temperature [ta] | 40 | 50 | 60 |
| | | Temperature at tc-point [°C] | 45 | 55 | 65 |
| | | Lifetime [h] | 100000 | 100000 | 100000 |
| | HE 14 W | ECG ambient temperature [ta] | 40 | 50 | 60 |
| | | Temperature at tc-point [°C] | 45 | 55 | 65 |
| | | Lifetime [h] | 100000 | 100000 | 100000 |
| | HO 24 W | ECG ambient temperature [ta] | 40 | 50 | 60 |
| | | Temperature at tc-point [°C] | 45 | 55 | 65 |
| | | Lifetime [h] | 100000 | 100000 | 100000 |

Additional product data

| | |
|---|-----------|
| Suitable for lamp power (1 lamp) | 14...24 W |
|---|-----------|

Capabilities

| | |
|---|---|
| Dimming interface | DALI / Touch DIM / Touch DIM Sensor |
| Dimming range | 1...100 % ¹⁾ |
| Dimmable | Yes |
| Overheating protection | Power reduction and switch off at $T > 75^{\circ}C$ at the tc point |
| Suitable for fixtures with prot. class | I |
| End of lamp life safety shutdown | EOL T.2 |
| Max. cable length to lamp/LED module | 1.0 m / 1.5 m |
| Intended for no-load operation | No |

¹⁾ Luminous flux

Certificates & standards

Product datasheet

| | |
|---------------------------|--|
| Approval marks – approval | VDE / VDE-EMC / EL / EAC / RCM / CCC |
| Standards | Acc. to EN 55015; EN 55022/Acc. to EN 61547/Acc. to IEC 61000-3-2/EN 61000-3-2/Acc. to EN 61347-2-3/Acc. to EN 60929/Acc. to EN 55015:2006 + A1:2007/Acc. to EN 61000-3-2/Acc. to EN 61547/Acc. to IEC 62386-101:Ed1/Acc. to IEC 62386-102:Ed1 |
| EEI – Energy Label | A1 BAT |
| Protection class | I |
| Type of protection | IP20 |



Logistical data

| | |
|----------------|--------------|
| Commodity code | 850410809000 |
|----------------|--------------|

Environmental information



| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) | |
|---|--|
| Date of Declaration | 14-04-2022 |
| Primary Article Identifier | 4050300870380 |
| Candidate List Substance 1 | Lead |
| CAS No. of substance 1 | 7439-92-1 |
| Safe Use Instruction | The identification of the Candidate List substance is sufficient to allow safe use of the article. |
| Declaration No. in SCIP database | 60e73f42-1e71-4b30-bc60-1a79326167b1 |

Wiring Diagram



319625_QTİ DALI 1x... DIM

493589_Touch DIM Function - e.g. QTİ DALI 1x... DIM



493590_Corridor Function - e.g. QTİ DALI 1x... DIM
















493666_DALI wiring diagram - e.g. QTİ DALI 1x... DIM

Product datasheet

Additional product information

- In order to achieve good radio interference suppression:1. Keep the cable between ECG and lamp as short as possible.2. The single lamp wires must be routed as close as possible to each other, whereas the lines of the different lamp ends must be routed separately.

Download Data

| File | |
|---|---|
|  | User instruction QUICKTRONIC QT _i T5 DALI DIM |
|  | Addon Technical Information 502689_Frequent switching Quicktronic |
|  | Addon Technical Information 502785_ECG lifetime - QUICKTRONIC (DALI) DIM |
|  | Product Datasheet 321525_ATI QT _i DALI 1x14-24 DIM (G+GB) |
|  | Certificates 335097_INOTEC |
|  | Certificates QT _i DALI VDE 40021252 210920 |
|  | Certificates 335135_Manufacturer's declaration – Burning-in of fluorescent lamps |
|  | Certificates 335153_Manufacturer's declaration – Low stand-by |
|  | Certificates 335154_Manufacturer's declaration – EN 55015:2006+A1:2007 (300 MHz) |
|  | Certificates 335169_Manufacturer's declaration – LampECG combinations: Frequent switching |
|  | Certificates 592319_EAC certificate for Quicktronics QT |
|  | Certificates 504208_VDE-EMC-CERTIFICATE QT _i DALI DIM |
|  | Declarations of conformity QUICKTRONIC DIM CE 3364258 190821 |
|  | Operating instructions 592411_EAC QT _i T5 DALI DIM |
|  | CAD data 3-dim 313432_360x30x21 1881281 |
|  | CAD data 3-dim 313433_360x30x21 1881281 |
|  | CAD data 3-dim 313453_360x30x21 1881281 |
|  | CAD data PDF 313406_360x30x21 1881281 |

Product datasheet

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|----------------------|------------------------------|--------------------------------------|----------------------|--------------|
| 4050300870380 | QTi DALI 1X14/24 DIM | Shipping carton box 20 | 392 mm x 165 mm x 98 mm | 6.34 dm ³ | 5680.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For more information on the system guarantee and the terms and conditions of the guarantee visit

▶ www.osram.com/system-guarantee

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

QTi DALI 1X14/24 DIM

QUICKTRONIC INTELLIGENT DALI DIM T5 | ECG dimmable DALI for FL 16 mm

| Product name | Lamp group | Nominal current | Nominal wattage + Power loss | Power factor λ [PIM] | Luminous flux at 35 °C | Number of lighting outlets |
|----------------------|--------------|-----------------|------------------------------|------------------------------|------------------------|----------------------------|
| QTi DALI 1X14/24 DIM | DULUX F 24 W | 0.11 A | 25.00 W | 0.98 | 1700 lm | 1 |
| | DULUX L 24 W | 0.11 A | 25.00 W | 0.98 | 1600 lm | 1 |
| | FC 22 W | 0.11 A | 25.00 W | 0.98 | 1750 lm | 1 |
| | HE 14 W | 0.07 A | 15.40 W | 0.95 | 1200 lm | 1 |
| | HO 24 W | 0.11 A | 25.30 W | 0.98 | 1750 lm | 1 |