

# Product family datasheet

## POWERSTAR HQI-TS

Metal halide lamps with quartz technology for enclosed luminaires



- Foyers, reception areas Factory and hall lighting with low-cost installations Exhibition halls and trade fairs Sports halls and multi-purpose halls Pedestrian zones, public squares Parks and gardens Buildings, monuments, bridges Approved only for use in enclosed luminaires Outdoor applications only in suitable luminaires

- High efficiency Uniform distribution of light Good to excellent color rendering Long lifetime Hot restrike capable UV values significantly below the maximum permitted thresholds to IEC 61167 thanks to UV filter



Product family datasheet

Technical data

	Electrical data	Photometrical data	Dimensions & weight		Additional product data	Certificates & standards	
Product description	Nominal current	Light color (designation)	Product weight	Overall length	Product remark	Energy efficiency class	Energy consumption
HQI-TS 400 W/D <sup>1)</sup>	4.1 A A	Daylight	88.00 g	205.60 mm	With NAV control gear	G	422.00 kWh/1000h

	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)			
Product description	Date of Declaration	Primary Article Identifier	Candidate List Substance 1	Declaration No. in SCIP database
HQI-TS 400 W/D <sup>1)</sup>	02-09-2022	4008321689191	No declarable substances contained	No declarable substances contained

<sup>1)</sup> With NAV control gear

---

HQI-TS 400 W/D

---

HQI-TS 400 W/D

---

### Application advice

For more detailed application information and graphics please see product datasheet.

---

### Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Product family datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321689191	HQI-TS 400 W/D	Shipping carton box 12	216 mm x 166 mm x 272 mm	9.75 dm <sup>3</sup>	1418.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner  
of LEDVANCE of LAMPS

**OSRAM**

OSRAM GmbH  
Marcel-Breuer-Strasse 6  
80807 Munich, Germany