

Product datasheet

NAV-T 250 W SUPER 4Y

VIALOX NAV-T SUPER 4Y | High-pressure sodium vapor lamps for open and enclosed luminaires



Product datasheet

Technical data


Electrical data

Ignition voltage	3.3/5.0 kVp
Nominal current	2.95 A A

Photometrical data

Rated LLMF at 2,000 h	0.98
Rated LLMF at 4,000 h	0.97
Rated LLMF at 6,000 h	0.96
Rated LLMF at 8,000 h	0.95
Rated LLMF at 12,000 h	0.94
Rated LLMF at 16,000 h	0.94
Rated LLMF at 20,000 h	0.94
Luminous flux	33200 lm

Dimensions & weight



Light center length (LCL)	158,0 mm
Product weight	135.00 g
Overall length	257.00 mm

Temperatures & operating conditions

Maximum permitted base edge temperature	250 °C
---	--------

Lifespan

Lifespan B50	36000 h
Lifespan B10	24000 h
Lifespan B5	20000 h

Product datasheet

Additional product data

Product remark	Important: Before replacing for NAV Standard lamps in existing installations, check that the igniters are suitable
Design / version	Clear
Mercury content	21.6 mg
Appropriate disposal acc. to WEEE	Yes

Capabilities

Burning position	Any
Enclosed luminaire required	No

Certificates & standards

Energy efficiency class	E
Energy consumption	267.00 kWh/1000h


Country specific categorizations

ILCOS	ST-250-H/E/SL-E40-47/257
-------	--------------------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-04-2022
Primary Article Identifier	4050300024417
Declaration No. in SCIP database	In work

Light Distribution



NAV_SUPER_4Y_SUPER_6Y

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300024417	NAV-T 250 W SUPER 4Y	Shipping carton box 12 Pieces Sleeves	241 mm x 324 mm x 200 mm	15.62 dm ³	2588.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For more information on the system guarantee and the terms and conditions of the guarantee visit

▶ www.osram.com/system-guarantee

Product datasheet

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany

NAV-T 250 W SUPER 4Y

VIALOX NAV-T SUPER 4Y | High-pressure sodium vapor lamps for open and enclosed luminaires

Product name	Product name ECG	EAN
NAV-T 250 W SUPER 4Y	PTo 250/220-240 3DIM	4008321863669