

Product datasheet NAV-T 250 W SUPER 4Y

VIALOX NAV-T SUPER 4Y | High-pressure sodium vapor lamps for open and enclosed luminaires







Technical data

Electrical data

Ignition voltage	3.3/5.0 kVp	
Nominal current	2.95 A A	

Photometrical data

Rated LLMF at 2,000 h	0.98
Rated LLMF at 4,000 h	0.97
Rated LLMF at 6,000 h	0.96
Rated LLMF at 8,000 h	0.95
Rated LLMF at 12,000 h	0.94
Rated LLMF at 16,000 h	0.94
Rated LLMF at 20,000 h	0.94
Luminous flux	33200 lm

Dimensions & weight

Light center length (LCL)	158,0 mm	
Product weight	135.00 g	
Overall length	257.00 mm	

Temperatures & operating conditions

Maximum permitted base edge temperature	250 °C

Lifespan

Lifespan B50	36000 h
Lifespan B10	24000 h
Lifespan B5	20000 h

Additional product data

Product remark	Important: Before replacing for NAV Standard lamps in existing installations, check that the igniters are suitable	
Design / version	Clear	
Mercury content	21.6 mg	
Appropriate disposal acc. to WEEE	Yes	

Capabilities

Burning position	Any	
Enclosed luminaire required	No	

Certificates & standards

Energy efficiency class	E	
Energy consumption	267.00 kWh/1000h	

Country specific categorizations

W 606	CT 250 11/5/CL 540 47/257
ILCOS	ST-250-H/E/SL-E40-47/257

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)				
Date of Declaration 18-04-2022				
Primary Article Identifier 4050300024417				
Declaration No. in SCIP database In work				

				••		
	a b			rıhı	1410	~
L	uı	н и	/ISLI	ııbı	utio	
	3					

NAV_SUPER_4Y_SUPER_6Y

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300024417	NAV-T 250 W SUPER 4Y	Shipping carton box 12 Pieces Sleeves	266 mm x 216 mm x 342 mm	19.65 dm³	2382.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For more information on the system quarantee and the terms and conditions of the quarantee visit https://

www.inventronics-light.com/multilevel-guarantees

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner of LEDVANCE of LAMPS



OSRAM GmbH Marcel-Breuer-Strasse 6 80807 Munich, Germany

NAV-T 250 W SUPER 4Y

VIALOX NAV-T SUPER 4Y | High-pressure sodium vapor lamps for open and enclosed luminaires