

# **Product datasheet** NAV-T 400 W SUPER 4Y

VIALOX NAV-T SUPER 4Y | High-pressure sodium vapor lamps for open and enclosed luminaires





April 28, 2024, 05:02:01 NAV-T 400 W SUPER 4Y

# Product datasheet

#### Technical data

# **Electrical data**

Ignition voltage	3.3/5.0 kVp
Nominal current	4.42 A A

#### Photometrical data

Rated LLMF at 2,000 h	0.98
Rated LLMF at 4,000 h	0.97
Rated LLMF at 6,000 h	0.96
Rated LLMF at 8,000 h	0.95
Rated LLMF at 12,000 h	0.94
Rated LLMF at 16,000 h	0.94
Rated LLMF at 20,000 h	0.94
Luminous flux	56500 lm

# **Dimensions & weight**

Light center length (LCL)	175,0 mm	
Product weight	150.00 g	
Overall length	285.00 mm	

# Temperatures & operating conditions

Maximum permitted base edge temperature	250 °C
---	--------

#### Lifespan

Lifespan B50	36000 h
Lifespan B10	24000 h
Lifespan B5	20000 h

# Product datasheet

#### Additional product data

Product remark	Important: Before replacing for NAV Standard lamps in existing installations, check that the igniters are suitable
Design / version	Clear
Mercury content	21.6 mg
Appropriate disposal acc. to WEEE	Yes

#### Capabilities

Burning position	Any
Enclosed luminaire required	No

#### **Certificates & standards**

Energy efficiency class	E
Energy consumption	416.00 kWh/1000h

# **Country specific categorizations**

ILCOS ST-4	400-H/E/SL-E40-47/285
------------	-----------------------

# **Environmental information**

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)				
Date of Declaration18-04-2022				
Primary Article Identifier	4050300281179			
Declaration No. in SCIP database In work				

NAV-T 400 W SUPER 4Y

### Light Distribution

NAV\_SUPER\_4Y\_SUPER\_6Y

#### Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300281179	NAV-T 400 W SUPER 4Y	Shipping carton box 12 Pieces Sleeves	266 mm x 216 mm x 342 mm	19.65 dm³	2552.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

For more information on the system guarantee and the terms and conditions of the guarantee visit https://

www.inventronics-light.com/multilevel-guarantees

# Product datasheet

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner of LEDVANCE of LAMPS



OSRAM GmbH Marcel-Breuer-Strasse 6 80807 Munich, Germany