

# SHARXS HTI 1200 W/D7/75

SharXS HTI | Metal halide lamps, double-ended



Areas of application

- Concert and effect lighting

#### Product family features

- High efficiency thanks to short-arc technology
- High thermal load capacity thanks to eXtreme Seal (XS) technology enables high pinch temperatures of up to 450 °C
- Hot restart capability
- Compact modular design the same dimensions for all wattages within each SharXS family
- Pre-focus base for accurate lamp installation



April 29, 2024, 10:03:09 SHARXS HTI 1200 W/D7/75

#### Technical data


#### **Electrical data**

Nominal wattage	120000 W	
Nominal voltage	953 V	
Ignition voltage	5.0 / 35 kVp	
Nominal current	126 A	
Lamp current	126 A	

### Photometrical data

Nominal luminous flux	91000 lm	
Luminance	41000 cd/cm <sup>2</sup>	
Color temperature	8800 K	
Color rendering index Ra	80	
Luminous efficacy	90 lm/W	

### **Dimensions & weight**



Diameter	210 mm	
Length	1360 mm	
Light center length (LCL)	57.5 mm	

### Temperatures & operating conditions

Maximum permitted pinch temperature	450 °C
-------------------------------------	--------

#### Lifespan

750 h

### Additional product data

Base (standard designation)	SFc10-4

Product remark	XS = eXtreme Seal (maximum permissible foil
	temperature 450 °C)

## Capabilities

**Burning position** 

Any

#### **Environmental information**

## Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

Date of Declaration 05-03-2024		
Primary Article Identifier	4008321285270	
Candidate List Substance 1	No declarable substances contained	
Declaration No. in SCIP database	No declarable substances contained	

### Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321285270	OSRHTI1200D775	-	-	-
4008321285287	OSRHTI1200D775	-	-	-

#### Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, SharXS lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321285270	SHARXS HTI 1200 W/D7/75	Shipping carton box 1	100 mm x 59 mm x 245 mm	1.45 dm³	124.00 g
4008321285287	SHARXS HTI 1200 W/D7/75	Shipping carton box 10	256 mm x 211 mm x 312 mm	16.85 dm³	1454.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.