

# SHARXS HTI 400 W/D3/75

SharXS HTI | Metal halide lamps, double-ended



### Areas of application

- Concert and effect lighting

#### Product family features

- High efficiency thanks to short-arc technology
- High thermal load capacity thanks to eXtreme Seal (XS) technology enables high pinch temperatures of up to 450 °C
- Hot restart capability
- Compact modular design the same dimensions for all wattages within each SharXS family
- Pre-focus base for accurate lamp installation







## Product datasheet

#### Technical data

### **Electrical data**


Nominal wattage	40000 W
Nominal voltage	500 V
Ignition voltage	3.0 / 25 kVp <sup>1)</sup>
Nominal current	85 A
Lamp current	85 A

<sup>1)</sup> Cold / Hot

#### Photometrical data

Nominal luminous flux	26000 lm	
Luminance	55000 cd/cm <sup>2</sup>	
Color temperature	7500 K	
Color rendering index Ra	80	

## **Dimensions & weight**



Diameter	1800 mm
Length	1360 mm
Light center length (LCL)	57.5 mm

## Temperatures & operating conditions

Maximum permitted pinch temperature	450 °C

### Lifespan

Lifespan	750 h
----------	-------

## Additional product data

## Product datasheet

Product remark	Also available as an OEM package with 30 units		
	without knurled nuts		

## Capabilities

### **Environmental information**

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)				
Date of Declaration 05-03-2024				
Primary Article Identifier	4008321911353   4008321285157			
Candidate List Substance 1	No declarable substances contained			
Declaration No. in SCIP database	In work			

## Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321285157	OSRHTI400SHARXSA	-	-	-
4008321285164	OSRHTI400SHARXSA	-	-	-

#### Product datasheet

#### Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, SharXS lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321285157	SHARXS HTI 400 W/D3/75	Shipping carton box 1	182 mm x 87 mm x 58 mm	0.92 dm³	94.00 g
4008321285164	SHARXS HTI 400 W/D3/75	Shipping carton box 10	256 mm x 211 mm x 312 mm	16.85 dm³	1424.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.