

## Lok-it!

HTI Short Arc Metal Halide lamps were designed as intense light sources primarily for moving head fixtures in the Entertainment marketplace.



### Areas of application

- Concert lighting
- Club & Disco
- Stage and theatre
- Studio, TV and film
- Architecture & Architainment

### Product family benefits


- Higher luminous efficacy than conventional HID lamps provides higher fixture efficiency
- Rapid relamping with bayonet lock

### Product family features

- Compact design and short arc gap for use in smaller and brighter fixtures
- Fast lamp replacement with one touch thanks to rotating lock
- Robust design with eXtreme Seal (XS) technology, allowing up to 450°C at the pinch seal
- Consistent lumen output over the life of the lamp
- Ceramic base allows high voltage up to 35 kV




## Product family datasheet



---

330962\_Lok-it! HSD 300W80P28



---

330963\_LOK-IT! HTI 1500 W60P50

## Product family datasheet

### Technical data

Product description	Electrical data null		Photometrical data null			Dimensions & weight null	
	Nominal voltage	Nominal current	Nominal luminous flux	Color temperature	Color rendering index Ra	Diameter	Length
Lok-it! HSD 300 W/80/P28	95.0 V		20500 lm	8000 K	> 85	23.0 mm	122.3 mm
Lok-it! HTI 400 W/60/P28	49.0 V	8 A	30000 lm	6000 K	> 85	17.0 mm	103.0 mm
Lok-it! HTI 700 W/60/P28	64.0 V	10 A	50000 lm	6000 K	> 75	18.0 mm	112.0 mm
Lok-it! HTI 700 W/75/P28	68.0 V	10.3 A	50000 lm	7500 K		20.0 mm	125.0 mm
Lok-it! HTI 700 W/75/P50	100 V	10 A	50000 lm	7500 K	85	25.0 mm	128.0 mm
Lok-it! HTI 1500 W/60/P50	100 V	15 A	130000 lm	6000 K	>85	29.0 mm	128.0 mm
Lok-it! HTI 1500 W/60/P50 M3W	100 V	15 A	130000 lm	6000 K		26.0 mm	128.0 mm
Lok-it! HTI 1600 W/60/P50	83.3 V	19.20 A	140000 lm	6000 K	95	26.0 mm	125.0 mm
Lok-it! HTI 2000 W/75/P50	100 V	20 A	155000 lm	7500 K	77	29.0 mm	130.0 mm
Lok-it! HTI 2000 W/60/P50	107 V	18.6 A	165000 lm	6000 K	95	29.0 mm	130.0 mm

Product description	Light center length (LCL)	Electrode gap cold	Lifespan null	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
			Lifespan	Date of Declaration	Primary Article Identifier
Lok-it! HSD 300 W/80/P28	67.0 mm	5.0 mm	2000 h	19-01-2022	4008321493989   4008321644831
Lok-it! HTI 400 W/60/P28	56.0 mm	3.4 mm	750 h	19-01-2022	4008321605481
Lok-it! HTI 700 W/60/P28	56.0 mm	4.1 mm	750 h	19-01-2022	4052899179790
Lok-it! HTI 700 W/75/P28	56.0 mm	4.0 mm	750 h	19-01-2022	4008321510549
Lok-it! HTI 700 W/75/P50	65.0 mm	4.0 mm	750 h	19-01-2022	4008321485205
Lok-it! HTI 1500 W/60/P50	65.0 mm	6.1 mm	750 h	19-01-2022	4008321553416   4052899561823
Lok-it! HTI 1500 W/60/P50 M3W	67.0 mm	7.0 mm	750 h	19-01-2022	4008321818997
Lok-it! HTI 1600 W/60/P50				19-01-2022	4062172123488
Lok-it! HTI 2000 W/75/P50			750 h	14-01-2022	4062172133111
Lok-it! HTI 2000 W/60/P50			750 h	14-01-2022	4062172133098

Product description	Candidate List Substance 1	Declaration No. in SCIP database
Lok-it! HSD 300 W/80/P28	No declarable substances contained	No declarable substances contained

## Product family datasheet

<b>Product description</b>	<b>Candidate List Substance 1</b>	<b>Declaration No. in SCIP database</b>
Lok-it! HTI 400 W/60/P28	No declarable substances contained	No declarable substances contained
Lok-it! HTI 700 W/60/P28	No declarable substances contained	No declarable substances contained
Lok-it! HTI 700 W/75/P28	No declarable substances contained	No declarable substances contained
Lok-it! HTI 700 W/75/P50	No declarable substances contained	No declarable substances contained
Lok-it! HTI 1500 W/60/P50	No declarable substances contained	In work
Lok-it! HTI 1500 W/60/P50 M3W	No declarable substances contained	No declarable substances contained
Lok-it! HTI 1600 W/60/P50	No declarable substances contained	No declarable substances contained
Lok-it! HTI 2000 W/75/P50	No declarable substances contained	No declarable substances contained
Lok-it! HTI 2000 W/60/P50	No declarable substances contained	No declarable substances contained

## Product family datasheet

---

### Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, Lok-it! lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

---

### Application advice

For more detailed application information and graphics please see product datasheet.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.