

# SIRIUS HRI 461 W S

## SIRIUS HRI | High-pressure discharge lamps with reflector



### Areas of application

- Concert lighting
- Club and disco
- Stage and theatre
- Studio, TV and film
- Architecture & Architainment

## Product family benefits

- Lightweight and compact reflector lamps
- Perfectly suited for small and lightweight moving heads
- Optimized burner design allows any burning position
- High luminance through very short arc and high pressure
- Bright light for brilliant light effects
- Long lifetime
- Easy lamp replacement
- Stable light output over the entire lifetime





## Product datasheet

### Technical data

## **Electrical data**

Nominal wattage	46100 W		
Nominal current	53 A		
Nominal voltage	830 V		

## Photometrical data

Nominal luminous flux	24000 lm		
Color temperature	7500 K		
Color rendering index Ra	80		

## Dimensions & weight

Diameter	600 mm
Length	670 mm
Arc length	1.3 mm

## Lifespan

Lifespan	1500 h

## Additional product data

<b>Category</b> VAL	LUE
---------------------	-----

## **Capabilities**

Burning position	Any
Working distance	37.4 mm

## **Environmental information**

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Date of Declaration 06-03-2024			
Primary Article Identifier	4052899532298   4052899553583		
Candidate List Substance 1	No declarable substances contained		
Declaration No. in SCIP database	No declarable substances contained		

### Product datasheet

#### Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, SIRIUS HRI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899532298	SIRIUS HRI 461 W S	Unpacked 1	- x - x -		140.00 g
4052899532304	SIRIUS HRI 461 W S	Shipping carton box 60	414 mm x 334 mm x 343 mm	47.43 dm³	9904.00 g
4052899553583	SIRIUS HRI 461 W S	Folding carton box 1	87 mm x 87 mm x 103 mm	0.78 dm <sup>3</sup>	188.00 g
4052899553590	SIRIUS HRI 461 W S	Shipping carton box 2	186 mm x 96 mm x 115 mm	2.05 dm <sup>3</sup>	422.00 g
4052899553606	SIRIUS HRI 461 W S	Shipping carton box 20	507 mm x 203 mm x 264 mm	27.17 dm³	4701.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.