Product datasheet



SIRIUS HRI 420 W

SIRIUS HRI | High-pressure discharge lamps with reflector



Areas of application

- Concert lighting
- Club and disco
- Stage and theatre
- Studio, TV and film
- Architecture & Architainment

Product family benefits

- Lightweight and compact reflector lamps
- Perfectly suited for small and lightweight moving heads
- Optimized burner design allows any burning position
- High luminance through very short arc and high pressure
- Bright light for brilliant light effects
- Long lifetime
- Easy lamp replacement
- Stable light output over the entire lifetime



April 25, 2024, 05:13:10 SIRIUS HRI 420 W

Product datasheet

Technical data

Electrical data

Nominal wattage	42000 W
Nominal current	5 A
Nominal voltage	700 V

Photometrical data

Nominal luminous flux	22000 lm
Color temperature	7700 К
Color rendering index Ra	85

Dimensions & weight

Diameter	580 mm
Length	720 mm

Lifespan

Lifespan 2500 h	Lifespan	2500 h
-----------------	----------	--------

Additional product data

Category	CORE
Capabilities	
Working distance	34.4 mm

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Date of Declaration 07-03-2024			
Primary Article Identifier	4062172192750 4062172192736		
Candidate List Substance 1	No declarable substances contained		
Declaration No. in SCIP database	In work		

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, SIRIUS HRI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

	-			
Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
SIRIUS HRI 420 W	Folding carton box 1	87 mm x 87 mm x 103 mm	0.78 dm³	178.00 g
SIRIUS HRI 420 W	Shipping carton box 2	186 mm x 96 mm x 115 mm	2.05 dm ³	402.00 g
SIRIUS HRI 420 W	Shipping carton box 20	507 mm x 203 mm x 264 mm	27.17 dm ³	4504.00 g
SIRIUS HRI 420 W	Shipping carton box 2	186 mm x 96 mm x 115 mm	2.05 dm ³	402.00 g
SIRIUS HRI 420 W	Shipping carton box 20	507 mm x 203 mm x 264 mm	27.17 dm³	4501.00 g
	SIRIUS HRI 420 W SIRIUS HRI 420 W SIRIUS HRI 420 W SIRIUS HRI 420 W	(Pieces/Unit)SIRIUS HRI 420 WFolding carton box 1SIRIUS HRI 420 WShipping carton box 2SIRIUS HRI 420 WShipping carton box 20SIRIUS HRI 420 WShipping carton box 20SIRIUS HRI 420 WShipping carton box 2SIRIUS HRI 420 WShipping carton box 2SIRIUS HRI 420 WShipping carton box 2	(Pieces/Unit)x width x height)SIRIUS HRI 420 WFolding carton box 187 mm x 87 mm x 103 mmSIRIUS HRI 420 WShipping carton box 2186 mm x 96 mm x 115 mmSIRIUS HRI 420 WShipping carton box 20507 mm x 203 mm x 264 mmSIRIUS HRI 420 WShipping carton box 20186 mm x 96 mm x 115 mmSIRIUS HRI 420 WShipping carton box 20507 mm x 203 mm x 115 mmSIRIUS HRI 420 WShipping carton box 2186 mm x 96 mm x 115 mmSIRIUS HRI 420 WShipping carton box 2187 mm x 20SIRIUS HRI 420 WShipping carton box 2507 mm x 203 mm x 203 mm x	(Pieces/Unit)x width x height)SIRIUS HRI 420 WFolding carton box 187 mm x 87 mm x 103 mm0.78 dm³SIRIUS HRI 420 WShipping carton box 2186 mm x 96 mm x 115 mm2.05 dm³SIRIUS HRI 420 WShipping carton box 20507 mm x 203 mm x 264 mm27.17 dm³SIRIUS HRI 420 WShipping carton box 20186 mm x 96 mm x 264 mm20.05 dm³SIRIUS HRI 420 WShipping carton box 2507 mm x 203 mm x 115 mm27.17 dm³SIRIUS HRI 420 WShipping carton box 2186 mm x 96 mm x 115 mm2.05 dm³SIRIUS HRI 420 WShipping carton box 2207 mm x 203 mm x 27.17 dm³2.017 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.