

64788 2000 W 240 V

Halogen studio lamps, single-ended



Areas of application

- Professional film and TV work
- Theater and concert stages
- Entertainment

Product family features

- Operation at mains voltage: 120 V | 230 V | 240 V
- Color temperature: 3,000 K (with longer lifespan)
- Color temperature: 3,200 K (for professional film and TV work)



April 25, 2024, 01:42:07 64788 2000 W 240 V

Technical data

Product information

| Order reference | 64788 CP/72 200 |
|-----------------|-----------------|
| | |

Electrical data


| Nominal wattage 200000 W | |
|--|-----------|
| Nominal voltage | 240 V |
| On-mode power | 2100.00 W |
| Energy consumption in on-mode 2100.0 kWh/1000h | |

Photometrical data

| Color rendering index Ra | 100 |
|------------------------------------|----------|
| Φuse value refers to luminous flux | 360 |
| Correlated color temperature CCT | 3150 К |
| Useful luminous flux (Физе) | 49340 lm |
| Chromaticity coordinate x | 0.427 |
| Chromaticity coordinate y | 0.400 |

Dimensions & weight





| Diameter | 350 mm |
|---------------------------|---------------------------|
| Length | 1450 mm |
| Light center length (LCL) | 70.0 mm |
| Illuminated field | 20.0*19.0 mm ² |
| Filament diameter | 19.0 mm |

Lifespan

| Lifespan | 400 h |
|----------|--------|
| Litespan | 11 001 |

Additional product data

| Base (standard designation) | GY16 |
|-----------------------------|------|
| Lighting technology used | HL |

Capabilities

Certificates & standards

| Energy efficiency class | G |
|-------------------------|---|
| | |

Country specific categorizations

| ANSI code | FTM | |
|-----------------|-----------------|--|
| LIF | CP/72 | |
| Order reference | 64788 CP/72 200 | |

Logistical data

Environmental information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) | | | | |
|---|---|--|--|--|
| Date of Declaration 22-04-2024 | | | | |
| Primary Article Identifier | 4050300283258 4008321098870 4008321632180 | | | |
| Candidate List Substance 1 | No declarable substances contained | | | |
| Declaration No. in SCIP database | In work | | | |

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|-----------------------|---------------------------------|---|----------------------|--------------|
| 4008321632180 | 64788 2000 W 240 V | Folding carton box 1 | 70 mm x 70 mm x 160 mm | 0.78 dm ³ | 110.00 g |
| 4008321984272 | 64788 2000 W 240 V | Shipping carton box 12 | 294 mm x 222 mm x 175 mm | 11.45 dm³ | 1524.81 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

A summary of studio lamps can be found on the halogen studio lamps poster. For more information on halogen lamps for studio, stage and TV see the brochure: "Good news for show business" "Halogen High Voltage Lamps" cross reference list

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.