

## XBO 6000 W/HTP XL OFR

XBO for cinema projection | Xenon short-arc lamps 450...10,000 W



### Areas of application

- Classic 35 mm film projection
- Digital film and video projection
- Architectural and effect light ("Light Finger")
- Sunlight simulation

### Product family benefits

- Short arc with very high luminance for brighter screen illumination
- Constant color temperature of 6,000 K throughout the entire lamp lifetime
- Easy to maintain
- High arc stability
- Instant light on screen thanks to hot restart function
- Wide dimming range

### Product family features

- Color temperature: approx. 6,000 K (Daylight)
- Wattage: 450...10,000 W
- Very good color rendering index:  $R_a >$




Technical data

Electrical data

Nominal current	160 A
Current control range	110...165 A
Nominal wattage	600000 W
Nominal voltage	370 V

Dimensions & weight



Diameter	780 mm
Length	4300 mm
Length with base excl. base pins/connection	382.00 mm
Light center length (LCL)	165.0 mm <sup>1)</sup>
Cable/wire length, input side	-
Electrode gap cold	9.0 mm
Product weight	93300 g

<sup>1)</sup> Distance from end of base to tip of electrode (cold)

Temperatures & operating conditions

Max. permitted ambient temp. pinch point	230 °C
--	--------

Lifespan

Lifespan	750 h
----------	-------

Additional product data

Base anode (standard designation)	SFa27-14
Base cathode (standard designation)	SFc27-14

Capabilities

Product datasheet

Cooling	Forced <sup>1)</sup>
Burning position	p15 <sup>2)</sup>

<sup>1)</sup> Vertical and horizontal  
<sup>2)</sup> For vertical burning position: anode (+) on top

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	05-03-2024
Primary Article Identifier	4008321412911
Declaration No. in SCIP database	In work

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321412911	XBO 6000 W/HTP XL OFR	Shipping carton box 1	590 mm x 229 mm x 234 mm	31.62 dm <sup>3</sup>	2019.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.