

XBO 3000 W/HTC OFR

XBO for cinema projection | Xenon short-arc lamps 450...10,000 W

Areas of application

- Classic 35 mm film projection
- Digital film and video projection
- Architectural and effect light ("Light Finger")
- Sunlight simulation

Product family benefits

- Short arc with very high luminance for brighter screen illumination
- Constant color temperature of 6,000 K throughout the entire lamp lifetime
- Easy to maintain
- High arc stability
- Instant light on screen thanks to hot restart function
- Wide dimming range

Product family features

- Color temperature: approx. 6,000 K (Daylight)
- Wattage: 450...10,000 W
- Very good color rendering index: R_a >



April 25, 2024, 01:42:07 XBO 3000 W/HTC OFR


Product datasheet

Technical data

Electrical data

Nominal current	3000 A
Current control range	60110 A
Nominal wattage	300000 W
Nominal voltage	290 V

Dimensions & weight



Diameter	6000 mm
Length	3980 mm
Electrode gap cold	6.0 mm
Product weight	64710 g

Temperatures & operating conditions

Max. permitted ambient temp. pinch point	230 °C
--	--------

Lifespan

Additional product data

Base anode (standard designation)	SFc28-13	
Base cathode (standard designation)	SFc28-13	
Product remark	OFR = Ozone-free version/H = Suitable for horizontal burning position/TC= Thread and cable	

Capabilities

Cooling	Forced
Burning position	Other ¹⁾

Product datasheet

 $^{1)}$ For vertical burning position: anode (+) on top

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)				
Date of Declaration 05-03-2024				
Primary Article Identifier	4008321064820			
Declaration No. in SCIP database	In work			

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321064820	OSRXBO3000HTCOFR	-	-	-

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321064820	XBO 3000 W/HTC OFR	Shipping carton box 1	590 mm x 229 mm x 234 mm	31.62 dm³	1914.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.