

# XBO 1600 W/HS XL OFR

XBO for cinema projection | Xenon short-arc lamps 450...10,000 W



#### Areas of application

- Classic 35 mm film projection
- Digital film and video projection
- Architectural and effect light ("Light Finger")
- Sunlight simulation

#### Product family benefits

- Short arc with very high luminance for brighter screen illumination
- Constant color temperature of 6,000 K throughout the entire lamp lifetime
- Easy to maintain
- High arc stability
- Instant light on screen thanks to hot restart function
- Wide dimming range

#### Product family features

- Color temperature: approx. 6,000 K (Daylight)
- Wattage: 450...10,000 W
- Very good color rendering index: R<sub>2</sub> >



January 29, 2024, 03:42:12 XBO 1600 W/HS XL OFR


# Product datasheet

## Technical data

## **Electrical data**

Nominal current	65 A
Current control range	5075 A
Nominal wattage	1600.00 W
Nominal voltage	23.0 V

### **Dimensions & weight**



Diameter	46.0 mm
Length	235.0 mm
Length with base excl. base pins/connection	205.00 mm
Light center length (LCL)	95.0 mm <sup>1)</sup>
Cable/wire length, input side	
Electrode gap cold	3.8 mm
Product weight	301.00 g

1) Distance from end of base to tip of electrode (cold)

Base cathode (standard designation)

## Temperatures & operating conditions

Max. permitted ambient temp. pinch point	230 °C	
Lifespan		
Lifespan	2500 h	
Additional product data		
Base anode (standard designation)	SFa27-11	

SFcX27-8

### Capabilities

# Product datasheet

Cooling	Forced
Burning position	s20/p20 <sup>1)</sup>

 $^{(1)}$  For vertical burning position: anode (+) on top

## **Environmental information**

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Date of Declaration	19-05-2023	
Primary Article Identifier	4008321299925	
Candidate List Substance 1	Lead	
CAS No. of substance 1	7439-92-1	
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.	
Declaration No. in SCIP database	4ED7A678-5BF0-416C-B869-898F17F9AE02	

# Product datasheet

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.