

HBO 1500 W/PIL

 $\label{thm:line} \mbox{HBO-IC Microlithography lamps for ASML i-line systems | Microlithography lamps fo$










Product datasheet

Technical data

Electrical data

Nominal voltage	23.0 V
Nominal current	6500 A
Type of current	DC
Rated wattage	1500.00 W
Nominal wattage	1500.00 W

Dimensions & weight



Diameter	46.0 mm
Length	273.0 mm
Mounting length	273.0 mm
Length with base excl. base pins/connection	240.00 mm
Light center length (LCL)	118.0 mm ¹⁾
Electrode gap cold	4.0 mm

 $^{^{1)}}$ Distance from end of base to tip of anode or cathode (cold)

Additional product data

Base anode (standard designation)	SFc30-6/25 ¹⁾
Base cathode (standard designation)	SFc27-10/35

 $^{^{1)}}$ Cooling fins and cable connection (M 8)

Capabilities

Cooling	Forced ¹⁾
Burning position	Other ²⁾

 $^{^{1)}}$ Maximum permissible base temperature: 200 $^{\circ}\mathrm{C}$

Environmental information

²⁾ Anode underneath

Product datasheet

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)				
Date of Declaration	05-03-2024			
Primary Article Identifier	4050300461465 4050300801308 4050300967103 4008321630872			
Candidate List Substance 1	Lead			
CAS No. of substance 1	7439-92-1			
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.			
Declaration No. in SCIP database	e22d7304-fdce-45fd-8d2a-6aa5291d1a5b d36bbc5d-42c8-43bc-a0b2-b64742e4d075 910a2e30-b741-4571-8470-190c5ee7888d			

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300461465	HBO 1500 W/PIL	Sliding sleeve 1	385 mm x 195 mm x 160 mm	12.01 dm³	1281.00 g
4050300461472	HBO 1500 W/PIL	Shipping carton box 6	510 mm x 420 mm x 420 mm	89.96 dm³	8600.00 g
4050300801308	HBO 1500 W/PIL	Sliding sleeve 1	- x - x -		
4050300801315	HBO 1500 W/PIL	Shipping carton box 6	510 mm x 420 mm x 420 mm	89.96 dm³	7520.00 g
4050300967103	HBO 1500 W/PIL	Shipping carton box	- x - x -		
4050300640334	HBO 1500 W/PIL	Shipping carton box	510 mm x 420 mm x 420 mm	89.96 dm³	2749.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.