

HBO 2510 W/NIL

 $\label{lem:hbo-ic} \mbox{HBO-IC Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox{Microlithography lamps for Nikon i-line systems} \ | \ \mbox$










Product datasheet

Technical data

Electrical data

Nominal voltage	23.0 V
Nominal current	109 A
Type of current	DC
Rated wattage	2500.00 W
Nominal wattage	2500.00 W

Dimensions & weight



Diameter	70.0 mm
Length	357.0 mm
Length with base excl. base pins/connection	325.00 mm
Light center length (LCL)	157.75 mm ¹⁾
Electrode gap cold	4.5 mm

 $^{^{1)}}$ Distance from end of base to tip of anode or cathode (cold)

Additional product data

Base anode (standard designation)	SFc33.5-12/50 ¹⁾
Base cathode (standard designation)	SFc33.5-14/50

¹⁾ With cable connection (M 8)

Capabilities

Cooling	Forced ¹⁾
Burning position	Other ²⁾

¹⁾ Maximum permissible base temperature: 200 °C $\,$

Environmental information

²⁾ Anode on top

Product datasheet

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)				
Date of Declaration	05-03-2024			
Primary Article Identifier	4050300947433 4050300628400			
Candidate List Substance 1	Lead			
CAS No. of substance 1	7439-92-1			
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.			
Declaration No. in SCIP database	df583275-90c5-465a-a872-03833323bf4a ff6ff5ad- e173-4d6b-9e5c-d3c870774670			

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300628400	HBO 2510 W/NIL	Folding carton box 1	605 mm x 320 mm x 230 mm	44.53 dm ³	3401.00 g
4050300739649	HBO 2510 W/NIL	Folding carton box 4	- x - x -		
4050300628417	HBO 2510 W/NIL	Shipping carton box	800 mm x 600 mm x 825 mm	396.00 dm ³	21782.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.