

HBO-IC Microlithography lamps for Canon LCD systems

Microlithography lamps for Canon LCD systems





327101_HBO 5000WCH

HBO MERCURY VAPOUR SHORT ARC LAMPS









Product family datasheet

Technical data

	Electrical da	Electrical data			Dimensions & weight	
Product description	Nominal	Nominal	Type of	Rated	Nominal	Diameter
	voltage	current	current	wattage	wattage	
HBO 5000 W/CH	640 V	78 A	DC	500000 W	500000 W	800 mm
HBO 8000 W/CHL	810 V	99 A	DC	800000 W	800000 W	1050 mm
HBO 8000 W/CHL2	790 V	101 A	DC	800000 W	800000 W	1050 mm

		Additional product data		Capabilities
Product description	Length with base excl. base pins/connection	Base anode (standard designation)	Base cathode (standard designation)	Burning position
HBO 5000 W/CH	338.00 mm	SFc33.5-50 ¹⁾	SFc33.5-12/50	Other ²⁾
HBO 8000 W/CHL	385.50 mm	SFaX40-13/50 ¹⁾	SFa40-12/45	Other ²⁾
HBO 8000 W/CHL2				Other

Environmental information
Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

Product description	Date of Declaration	Primary Article Identifier	Candidate List Substance 1	CAS No. of substance
HBO 5000 W/CH	05-03-2024	4008321381385 4008321381934	Lead	7439-92-1
HBO 8000 W/CHL	05-03-2024	4008321545756	Lead	7439-92-1
HBO 8000 W/CHL2	06-03-2024	4052899168848	Lead	7439-92-1

Product description	Safe Use Instruction	Declaration No. in SCIP database
нво 5000 w/сн	The identification of the Candidate List substance is sufficient to allow safe use of the article.	6a892f46-a7cc-45de- afbd-e023484ba64d 5767a2be-1efc-43e6- b1b6-bce7aa003303
HBO 8000 W/CHL	The identification of the Candidate List substance is sufficient to allow safe use of the article.	e99f1f0e-22f8-43bf- ae0a-417bc48f22ff
HBO 8000 W/CHL2	The identification of the Candidate List substance is sufficient to allow safe use of the article.	744ef11b-de39- 4209-a666- 75f0acf4935a

¹⁾ With cable connection (M 10)

²⁾ Anode on top

Product family datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.