

## HBO 250 W/LS

HBO-IC Microlithography lamps for other systems | Microlithography lamps for other systems




Technical data

Electrical data

Nominal voltage	390 V
Nominal current	64 A
Type of current	DC
Rated wattage	25000 W
Nominal wattage	25000 W

Dimensions & weight



Diameter	200 mm
Length	1470 mm
Length with base excl. base pins/connection	127.00 mm
Light center length (LCL)	62.0 mm <sup>1)</sup>
Electrode gap cold	2.0 mm

<sup>1)</sup> Distance from end of base to tip of anode or cathode (cold)

Additional product data

Base anode (standard designation)	SFa13-5/20
Base cathode (standard designation)	Special

Capabilities

Cooling	Convection <sup>1)</sup>
Burning position	Other <sup>2)</sup>

<sup>1)</sup> Maximum permissible base temperature: 230 °C

<sup>2)</sup> Anode underneath

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
---

Product datasheet

Date of Declaration	05-03-2024
Primary Article Identifier	4008321336668   4052899514843
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	872b1190-ab05-48f3-8283-61ef79b983c3   c2f27551-e9f2-44a8-9229-f4eeb5f6fb66

## Product datasheet

### Safety advice

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321336668	HBO 250 W/LS	Shipping carton box 1	224 mm x 95 mm x 60 mm	1.28 dm <sup>3</sup>	270.00 g
4008321336675	HBO 250 W/LS	Shipping carton box 10	306 mm x 235 mm x 200 mm	14.38 dm <sup>3</sup>	3087.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.