

# Product datasheet

## PP LEDSPOT 111 1180 W/930 G53

**PARATHOM PRO LEDspot 111 | LED reflector lamps AR111 with retrofit pin base**

- Shops and exhibition rooms Domestic applications  
Commercial applications Accent lighting Outdoor use in  
outdoor luminaires only (minimum IP65)



- Quick, simple and safe replacement without rewiring Design, dimensions, luminous flux comparable to an incandescent or halogen lamp Low maintenance costs thanks to long lifetime No UV and near-IR radiation in the light beam Stepless dimming Very high dimmer compatibility, see also "[www.ledvance.com/dim](http://www.ledvance.com/dim)" Compatible with many common conventional and electronic control gears (see also "compatibility list") Instant 100 % light, no warm-up time



Technical data

Electrical data

Rated wattage	11.80 W
Nominal wattage	11.80 W
Nominal voltage	12 V
Claimed equiv. conventional lamp power	50 W
Operating frequency	50...60 Hz
Max. lamp no. on circuit break. 10 A (B)	16
Max. lamp no. on circuit break. 16 A (B)	24
Nominal current	1.4 A

Photometrical data

Nominal luminous flux	650 lm
Rated luminous flux	650 lm
Rated color temperature	3000 K
Color rendering index Ra	97
Light color (designation)	Warm White
Standard deviation of color matching	≤5 sdcn
Nominal useful luminous flux 90°	710 lm
Rated useful luminous flux 90°	650 lm
Rated peak intensity	1600 cd
Color temperature	3000 K
Luminous flux	650 lm
Lumen main.fact.at end of nom.life time	0.70

Light technical data

Beam angle	40 °
Nominal beam angle	40 °
Rated beam angle (half peak value)	40.00 °
Starting time	< 0.5 s

Dimensions & weight

Overall length	55.0 mm
Diameter	110.7 mm
Outer bulb	AR111
Product weight	215.00 g
Length	55.0 mm
Maximum diameter	111.0 mm

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Lifespan

Nominal lamp life time	40000 h
Rated lamp life time	40000 h
Number of switching cycles	100000
Lumen maintenance at end of service life	0.70

Additional product data

Base (standard designation)	G53
Mercury content	0.0 mg
Mercury-free	Yes
Appropriate disposal acc. to WEEE	Yes
Successor EAN	4058075448445
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmable	Yes
----------	-----

Certificates & standards

Energy efficiency class	A
Energy consumption	13 kWh/1000h
Type of protection	IP20

Country specific categorizations

Order reference	LPAR111 5040 11
-----------------	-----------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-04-2022
Primary Article Identifier	4058075264496
Declaration No. in SCIP database	In work

## Product datasheet

---

### Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

---

### References / Links

For dimming conformity see

▶ [www.osram.com/DIM](http://www.osram.com/DIM)

For Guarantee see [https://](https://www.inventronics-light.com/multilevel-guarantees)

▶ [www.inventronics-light.com/multilevel-guarantees](https://www.inventronics-light.com/multilevel-guarantees)

For further products and actual information concerning LED lamps see

▶ [www.osram.com/ledlamps](http://www.osram.com/ledlamps)

Further information see

▶ [www.osram.com/low-voltage-ledlamps](http://www.osram.com/low-voltage-ledlamps)

---

### Disclaimer

— Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner  
of LEDVANCE of LAMPS

**OSRAM**

OSRAM GmbH  
Marcel-Breuer-Strasse 6  
80807 Munich, Germany