

SUPER H4

Up to 30% more light





Up to 30% more light For better visibility and shorter reaction times compared to standard halogen lamps



Enhanced illumination For extra confidence



Convincing price-performance ratio For better visibility at a reasonable price



Up to 30% more light on the road

SUPER headlight lamps offer more performance for the most important lamp types. With up to 30% more light compared to standard lamps, signs, obstacles and hazards are more rapidly recognized.

Technical data

Product information

Order reference	64193SUP	
Application (Category and Product specific)	Halogen headlight lamp	

Electrical data


Power input	75 / 68 W ¹⁾
Nominal voltage	12.0 V
Nominal wattage	60/55 W
Test voltage	13.2 V

¹⁾ Maximum

Photometrical data

Luminous flux	1700/1075 lm
Luminous flux tolerance	±10 / ±7 %

Dimensions & weight



Diameter	17.0 mm
Product weight	25.60 g
Length	82.0 mm

Lifespan

Lifespan B3	150 / 150 h ¹⁾
Lifespan Tc	350 / 350 h ¹⁾

¹⁾ Filament 1 / Filament 2

Additional product data

Base (standard designation)	P43t
-----------------------------	------

Capabilities

Technology	HAL		
Certificates & standards			
ECE category	H4		
Country specific categorizations			
Order reference	64193SUP		

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

Date of Declaration 05-03-2024		
Primary Article Identifier 4050300478104 4050300467245 400832		
Candidate List Substance 1	No declarable substances contained	
Declaration No. in SCIP database	In work	

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300467245	OSRA64193SUP	-	-	-
4050300467252	OSRA64193SUP	-	-	-
4050300467245	OSRA64193SUP	-	-	-

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300467245	SUPER H4	Folding carton box 1	- x - x -		
4050300467252	SUPER H4	Bundle 10	- x - x -		
4050300467269	SUPER H4	Shipping carton box 100	485 mm x 250 mm x 160 mm	19.40 dm³	3643.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.





人家









1.0, ⊙ 2. ⊂=10 ↔ [

