

OSRAM ORIGINAL LINE

Original spare part



The cost-effective original spare parts

OSRAM ORIGINAL LINE halogen lamps offer convincing performance for standard requirements, are robust and cost-effective. They have already been successfully used in millions of new cars from renowned manufacturers, whether as standard initial equipment or original spare parts. Convince yourself of the excellent value for money, the reliable OEM quality and the wide product range of the ORIGINAL LINE.

Product family datasheet

Technical data

Product description	Product information		Electrical data			
	Order reference	Application (Category and Product specific)	Power input	Nominal voltage	Nominal wattage	Test voltage
OSRAM ORIGINAL LINE H27/2W	881	Halogen headlight lamp	31 W ³⁾	12.0 V	27.00 W	13.5 V
OSRAM ORIGINAL LINE H8B	64242	Halogen headlight lamp	43 W ³⁾	12.0 V	35.00 W	13.2 V
OSRAM ORIGINAL LINE HB1	9004	Halogen headlight lamp	70 / 50 W ³⁾	12.8 V	65/45 W	12.8 V
OSRAM ORIGINAL LINE H16	64219L+	Halogen headlight lamp	26 W ³⁾	12.0 V	19.00 W	13.2 V
OSRAM ORIGINAL LINE H9B	64243	Halogen headlight lamp	73 W ³⁾	12.0 V	65.00 W	13.2 V
OSRAM ORIGINAL LINE H10 ¹⁾	9145	Halogen headlight lamp	50 W ³⁾	12.0 V	42.00 W	13.2 V
OSRAM ORIGINAL LINE H13 ¹⁾	64178	Halogen headlight lamp	75 / 68 W ³⁾	12.0 V	60/55 W	13.2 V
OSRAM ORIGINAL LINE H4	64193	Halogen headlight lamp	75 / 68 W ³⁾	12.0 V	60/55 W	13.2 V
OSRAM ORIGINAL LINE H8 ¹⁾	64212	Halogen headlight lamp	43 W ³⁾	12.0 V	35.00 W	13.2 V
OSRAM ORIGINAL LINE H7 ¹⁾	64210	Halogen headlight lamp	58 W ³⁾	12.0 V	55.00 W	13.2 V
OSRAM ORIGINAL LINE H3 ¹⁾	64151	Halogen headlight lamp	68 W ³⁾	12.0 V	55.00 W	13.2 V
OSRAM ORIGINAL LINE H11	64211	Halogen headlight lamp	62 W ³⁾	12.0 V	55.00 W	13.2 V
OSRAM ORIGINAL LINE H11B	64241	Halogen headlight lamp	62 W ³⁾	12.0 V	55.00 W	13.2 V
OSRAM ORIGINAL LINE H27/1W	880	Halogen headlight lamp	31 W ³⁾	12.0 V	27.00 W	13.5 V
OSRAM ORIGINAL LINE HB3 ¹⁾	9005	Halogen headlight lamp	73 W ³⁾	12.0 V	60.00 W	13.2 V
OSRAM ORIGINAL LINE HB3A ¹⁾	9005XS	Halogen headlight lamp	73 W ³⁾	12.0 V	60.00 W	13.2 V
OSRAM ORIGINAL LINE HB4 ¹⁾	9006		62 W ³⁾	12.0 V	51.00 W	13.2 V
OSRAM ORIGINAL LINE HB4	9006XS	Halogen headlight lamp	62 W ³⁾	12.0 V	51.00 W	13.2 V
OSRAM ORIGINAL LINE R2 ²⁾	64183	Halogen headlight lamp	57 / 51 W ³⁾	12.0 V	45/40 W	13.2 V
OSRAM ORIGINAL LINE HIR1	9011	Halogen headlight lamp		12.0 V	65.00 W	13.2 V
OSRAM ORIGINAL LINE HIR2	9012	Halogen headlight lamp	60 W ³⁾	12.0 V	55.00 W	13.2 V
OSRAM ORIGINAL LINE H1 ¹⁾	64150	Halogen headlight lamp	68 W ³⁾	12.0 V	55.00 W	13.2 V
OSRAM ORIGINAL LINE H2	64173	Halogen headlight lamp	68 W ³⁾	12.0 V	55.00 W	13.2 V
OSRAM ORIGINAL LINE HB5	9007	Halogen headlight lamp	70 / 60 W ³⁾	12.8 V	65/55 W	12.8 V

Product family datasheet

Product description	Product information		Electrical data			
	Order reference	Application (Category and Product specific)	Power input	Nominal voltage	Nominal wattage	Test voltage
OSRAM ORIGINAL LINE H9 ¹⁾	64213	Halogen headlight lamp	73 W ³⁾	12.0 V	65.00 W	13.2 V
OSRAM ORIGINAL LINE H15 ¹⁾	64176	Halogen headlight lamp	64 / 19 W ³⁾	12.0 V	55/15 W	13.2 V

Product description	Photometrical data		Dimensions & weight	Additional product data	Capabilities	Certificates & standards
	Luminous flux	Luminous flux tolerance	Diameter	Base (standard designation)	Technology	ECE category
OSRAM ORIGINAL LINE H27/2W	450 lm	±15 %	9 mm	PGJ13	Halogen lamp	H27/2W
OSRAM ORIGINAL LINE H8B	800 lm	±15 %	12.0 mm	PGJY19-1	Halogen lamp	H8B
OSRAM ORIGINAL LINE HB1	700 lm	±10 / ±10 %	16.0 mm	P29t	Halogen lamp	HB1
OSRAM ORIGINAL LINE H16	500 lm	+10 %...15 %	10.0 mm		Halogen lamp	H16
OSRAM ORIGINAL LINE H9B	2100 lm	±10 %	12.0 mm	PGJY19-5	Halogen lamp	H9B
OSRAM ORIGINAL LINE H10 ¹⁾	850 lm	±15 %	12.0 mm	PY20d	Halogen lamp	H10
OSRAM ORIGINAL LINE H13 ¹⁾	1000 lm	±15 / ±15 %	17.0 mm	P26.4t	Halogen lamp	H13
OSRAM ORIGINAL LINE H4	1650/1000 lm	±12 / ±15 %	17.0 mm	P43t	Halogen lamp	H4
OSRAM ORIGINAL LINE H8 ¹⁾	800 lm	±15 %	12.0 mm	PGJ19-1	Halogen lamp	H8
OSRAM ORIGINAL LINE H7 ¹⁾	1500 lm	±10 %	12.0 mm	PX26d	Halogen lamp	H7
OSRAM ORIGINAL LINE H3 ¹⁾	1450 lm	±15 %	11.5 mm	PK22s	Halogen lamp	H3
OSRAM ORIGINAL LINE H11	1350 lm	±10 %	12.0 mm	PGJ19-2	Halogen lamp	H11
OSRAM ORIGINAL LINE H11B	1350 lm	±10 %	12.0 mm	PGJY19-2	Halogen lamp	H11B
OSRAM ORIGINAL LINE H27/1W	450 lm	±15 %	9 mm	PG13	Halogen lamp	H27/1W
OSRAM ORIGINAL LINE HB3 ¹⁾	1700 lm	±12 %	12.0 mm	P20d	Halogen lamp	HB3
OSRAM ORIGINAL LINE HB3A ¹⁾	1860 lm	±12 %	12.0 mm	P20d	Halogen lamp	HB3A
OSRAM ORIGINAL LINE HB4 ¹⁾	1000 lm	±15 %	12.0 mm	P22d	Halogen lamp	HB4
OSRAM ORIGINAL LINE HB4	1095 lm	±15 %	12.0 mm	P22d	Halogen lamp	HB4
OSRAM ORIGINAL LINE R2 ²⁾	1030/675 lm	±15 %	17.0 mm	P45t	Halogen lamp	R2
OSRAM ORIGINAL LINE HIR1	2500 lm	±15 %	11.3 mm	PX20d	Halogen lamp	HIR1
OSRAM ORIGINAL LINE HIR2	1875 lm	±15 %	11.3 mm	PX22d	Halogen lamp	HIR2
OSRAM ORIGINAL LINE H1 ¹⁾	1550 lm	±15 %	9 mm	P14.5s	Halogen lamp	H1
OSRAM ORIGINAL LINE H2	1800 lm	±15 %	9 mm	X511	Halogen lamp	H2
OSRAM ORIGINAL LINE HB5	1000 lm	±10 / ±10 %	16.0 mm	PX29t	Halogen lamp	HB5
OSRAM ORIGINAL LINE H9 ¹⁾	2100 lm	±10 %	12.0 mm	PGJ19-5	Halogen lamp	H9
OSRAM ORIGINAL LINE H15 ¹⁾	260/1350 lm	±10 / ±10 %	13.0 mm	PGJ23t-1	Halogen lamp	H15

Product family datasheet

- 1) Lamp complies with ECE R 37 and SAE (DOT) regulations
- 2) Successor to BILUX AS lamp (product reference 7951)
- 3) Maximum

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

The OSRAM logo is displayed in a bold, orange, sans-serif font.