OSRAM

DIADEM CHROME WY5W

Only amber during operation

Chrome design
Thanks to cutting edge interference and absorber coating

Amber when ON
Only amber when operating, otherwise almost invisible

Homogenous appearance
Reflector has a fully homogenous chrome look

The design light with chrome look

OSRAM DIADEM CHROME signal lamps have a strikingly exclusive design: their chrome look made possible by a cutting edge interference and absorber coating. The lamps emit amber light only when operational. At other times, they are almost invisible and have no irritating color effects. DIADEM CHROME lamps are ideal for all indicator lights with clear covers.

Technical data

Product information

Application (Category and Product specific)	Auxiliary lamp

General Product Information

Global order reference	2827DC

Electrical Data

Power input	5 W
Nominal voltage	12.0 V
Nominal wattage	5 W
Test voltage	13.5 V
Power input tolerance	±10 %

Photometric Data

Nominal luminous flux	30 lm
Luminous flux tolerance	±20 %

Physical Attributes & Dimensions

Diameter	10.0 mm
Product weight	1.35 g
Length	26.8 mm
Lamp base	W2.1x9.5d

Lifetime Data

Lifespan B3	200 hr
Lifespan Tc	500 hr

Capabilities

Technology	AUX

Certificates & standards

ECE category	WY5W

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Date of declaration	09-07-2024

Product datasheet

Primary article identifier	4052899417939 | 4052899979925 | 4008321972750 | 4052899417915 | 4062172394758 | 4052899417953 | 4052899067790
Candidate list substance 1	No declarable substances contained
Declaration no. in SCIP database	In work

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321972767	DIADEM CHROME WY5W		- x - x -	1.13 dm³	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM