OSRAM

DIADEM CHROME PY21W

Only amber during operation



Chrome design Thanks to cutting edge interference and absorber coating

Amber when ON

Only amber when operating, otherwise Reflector has a fully homogenous chrome almost invisible



The design light with chrome look

OSRAM DIADEM CHROME signal lamps have a strikingly exclusive design: their chrome look made possible by a cutting edge interference and absorber coating. The lamps emit amber light only when operational. At other times, they are almost invisible and have no irritating color effects. DIADEM CHROME lamps are ideal for all indicator lights with clear covers.

Homogenous appearance

look

Product datasheet

Technical data

Product information

Order reference	7507DC	
Application (Category and Product specific)	Auxiliary lamp	

Electrical data

Power input	25 W
Nominal voltage	12.0 V
Nominal wattage	21.00 W
Test voltage	13.5 V
Power input tolerance	±6 %

Photometrical data

Luminous flux	280 lm
Luminous flux tolerance	±20 %

Dimensions & weight



Diameter	25.0 mm
Product weight	8.00 g
Length	52.6 mm

Lifespan

Lifespan B3	100 h
Lifespan Tc	250 h

Additional product data

Base (standard designation)	BAU15s

Product datasheet

Capabilities

Technology	AUX
------------	-----

Certificates & standards

ECE category	PY21W
Approval marks – approval	E1 approval

Country specific categorizations

Order reference	7507DC

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Date of Declaration	05-03-2024		
Primary Article Identifier	4008321972774 4052899241657 4052899417977 4052899418011 4062172211529 4062172271950 4052899979918 4062172394857		
Candidate List Substance 1	No declarable substances contained		
Declaration No. in SCIP database	In work		

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321972774	DIADEM CHROME PY21W	Blister 2	- x - x -		
4008321972781	DIADEM CHROME PY21W	Shipping carton box 20	279 mm x 115 mm x 146 mm	4.68 dm³	360.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.













Product datasheet

OSRAM