

DIADEM PR21W

Only amber or red during operation



Opal design

Thanks to state-of-the-art interference coating



Amber or red when ON

Only amber or red when operating



Extra lifetime

Up to double the service life compared with standard lamps



The design light with opal look

OSRAM DIADEM signal lights only emit amber or red light during operation – making them the perfect, attractive light supplement for halogen and xenon headlamps. Thanks to the state-of-the-art interference coating, the lamp shines in an opal look and is ideal for all indicator lights with clear covers. In addition, it convinces with up to double the service life compared to standard lamps.

Product datasheet

Technical data

Product information

Order reference	7508LDR
Application (Category and Product specific)	Auxiliary lamp


Electrical data

Power input	25 W
Nominal voltage	12.0 V
Nominal wattage	21.00 W
Test voltage	13.5 V
Power input tolerance	±6 %

Photometrical data

Luminous flux	110 lm
Luminous flux tolerance	±20 %

Dimensions & weight



Diameter	27.0 mm
Product weight	7.68 g
Length	52.6 mm

Lifespan

Lifespan B3	500 h
Lifespan Tc	1000 h

Additional product data

Base (standard designation)	BAW15s
-----------------------------	--------

Product datasheet

Certificates & standards

ECE category	PR21W
--------------	-------

Country specific categorizations

Order reference	7508LDR
-----------------	---------

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4008321376848	OSRA7508LDRBLI1	-	-	-
4008321376848	OSRA7508LDRBLI1	-	-	-

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321376848	DIADEM PR21W	Blister 1	135 mm x 95 mm x 35 mm	0.45 dm ³	29.68 g
4008321376855	DIADEM PR21W	Shipping carton box 10	279 mm x 148 mm x 118 mm	4.87 dm ³	271.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM