

## ULTRA LIFE

Up to four times longer lifetime




### Extra lifetime

Up to four times longer lifetime compared to standard auxiliary lamps



### More durability

For longer replacement cycles and additional reliability and comfort



### Wide product range

Fits for most common auxiliary lamp types



### The durable light with up to four times longer lifetime

With ULTRA LIFE, you choose durable signal lamps for your car. The lamps provide a long life span - up to four times longer lifetime compared to standard lamps - and last up to 100,000 km (with an average annual mileage of 14,259 km and 60% light on). They are therefore ideal for frequent drivers.

# Product family datasheet

## Technical data

| Product description            | Electrical Data    |                 |                 |              | Photometric Data      |
|--------------------------------|--------------------|-----------------|-----------------|--------------|-----------------------|
|                                | Power input        | Nominal voltage | Nominal wattage | Test voltage | Nominal luminous flux |
| ULTRA LIFE C5W                 | 5 W                | 12 V            | 5 W             | 13.5 V       | 45 lm                 |
| ULTRA LIFE H6W                 | 7 W                | 12 V            | 6 W             | 13.5 V       | 125 lm                |
| ULTRA LIFE P21/5W              | 25 / 6 W           | 12 V            | 21/5 W          | 13.5 V       | 440/35 lm             |
| ULTRA LIFE P21W                | 25 W               | 12 V            | 21 W            | 13.5 V       | 460 lm                |
| ULTRA LIFE PY21W <sup>1)</sup> | 25 W               | 12 V            | 21 W            | 13.5 V       | 280 lm                |
| ULTRA LIFE R10W                | 10 W               | 12 V            | 10 W            | 13.5 V       | 125 lm                |
| ULTRA LIFE R5W                 | 5 W                | 12 V            | 5 W             | 13.5 V       | 50 lm                 |
| ULTRA LIFE W5W                 | 5 W                | 12 V            | 5 W             | 13.5 V       | 50 lm                 |
| ULTRA LIFE HY21W               | 25 W <sup>3)</sup> | 12 V            | 21 W            | 13.5 V       | 300 lm                |

| Product description            | Luminous flux tolerance | Physical Attributes & Dimensions | Lifetime Data               |                             | Certificates & standards | Environmental & Regulatory Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |
|--------------------------------|-------------------------|----------------------------------|-----------------------------|-----------------------------|--------------------------|--|
|                                |                         | Diameter                         | Lifespan B3                 | Lifespan Tc                 | ECE category             | Primary article identifier   |
| ULTRA LIFE C5W                 | ±20 %                   | 11.0 mm                          | 1500 hr                     | 4000 hr                     | C5W                      | 4008321415240   4062172394819   4008321415264   4008321413086   4052899419629                    |
| ULTRA LIFE H6W                 | ±12 %                   | 9 mm                             | 600 hr                      | 1000 hr                     | H6W                      | 4052899494039   4052899419681   4008321415325   4008321413178   4062172394796                    |
| ULTRA LIFE P21/5W              | ±15 / ±20 %             | 25.0 mm                          | 300 / 3000 hr <sup>2)</sup> | 800 / 6000 hr <sup>2)</sup> | P21/5W                   | 4008321415288   4062172394895   4008321413116   4008321415301                                    |
| ULTRA LIFE P21W                | ±15 %                   | 25.0 mm                          | 500 hr                      | 1000 hr                     | P21W                     | 4008321415141   4062172394833   4008321415349  |
| ULTRA LIFE PY21W <sup>1)</sup> | ±20 %                   | 25.0 mm                          | 500 hr                      | 1000 hr                     | PY21W                    | 4008321415165   4062172394871   4008321413147  |
| ULTRA LIFE R10W                | ±20 %                   | 16.0 mm                          | 600 hr                      | 1200 hr                     | R10W                     | 4062172394918   4008321415226   4008321416568   4008321415400                                    |
| ULTRA LIFE R5W                 | ±20 %                   | 16.0 mm                          | 600 hr                      | 1200 hr                     | R5W                      | 4008321415370   4008321416537   4008321415202   4062172394772                                    |

## Product family datasheet

| Product description | Luminous flux tolerance | Physical Attributes & Dimensions | Lifetime Data |             | Certificates & standards | Environmental & Regulatory Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |
|---------------------|-------------------------|----------------------------------|---------------|-------------|--------------------------|--|
|                     |                         | Diameter                         | Lifespan B3   | Lifespan Tc | ECE category             | Primary article identifier   |
| ULTRA LIFE W5W      | ±20 %                   | 10.0 mm                          | 700 hr        | 1500 hr     | W5W                      | 4062172394734   4008321413024   4008321415189  |
| ULTRA LIFE HY21W    | ±17 %                   | 9 mm                             | 400 hr        | 700 hr      | HY21W                    | 4052899910256   4052899910744  |

| Product description            | Candidate list substance 1         | Declaration no. in SCIP database   |
|--------------------------------|------------------------------------|------------------------------------|
| ULTRA LIFE C5W                 | No declarable substances contained | No declarable substances contained |
| ULTRA LIFE H6W                 | No declarable substances contained | No declarable substances contained |
| ULTRA LIFE P21/5W              | No declarable substances contained | No declarable substances contained |
| ULTRA LIFE P21W                | No declarable substances contained | No declarable substances contained |
| ULTRA LIFE PY21W <sup>1)</sup> | No declarable substances contained | No declarable substances contained |
| ULTRA LIFE R10W                | No declarable substances contained | No declarable substances contained |
| ULTRA LIFE R5W                 | No declarable substances contained | No declarable substances contained |
| ULTRA LIFE W5W                 | No declarable substances contained | No declarable substances contained |
| ULTRA LIFE HY21W               | No declarable substances contained | No declarable substances contained |









<sup>1)</sup> Amber lamp for clear indicators

<sup>2)</sup> Filament 1

<sup>3)</sup> Maximum

## Product family datasheet

### Download Data

| File  |   |
|---|---|
|  | User instruction<br>GPRS_Safety symbols instructions          |
|  | Addon Technical Information<br>Product Certificates AUX       |
|  | ref_pim_amsproduct360degreeimages<br>ULTRA LIFE C5W 6418ULT   |
|  | ref_pim_amsproduct360degreeimages<br>ULTRA LIFE P21W 7506ULT  |
|  | ref_pim_amsproduct360degreeimages<br>ULTRA LIFE PY21W 7507ULT |
|  | ref_pim_amsproduct360degreeimages<br>ULTRA LIFE R10W 5008ULT  |
|  | ref_pim_amsproduct360degreeimages<br>ULTRA LIFE R5W 5007ULT   |
|  | ref_pim_amsproduct360degreeimages<br>ULTRA LIFE W5W 2825ULT   |

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

