OSRAM

ULTRA LIFE HY21W

Up to four times longer lifetime





Extra lifetime

Up to four times longer lifetime compared to standard auxiliary lamps



More durability

For longer replacement cycles and additional reliability and comfort



Wide product range

Fits for most common auxiliary lamp types



The durable light with up to four times longer lifetime

With ULTRA LIFE, you choose durable signal lamps for your car. The lamps provide a long life span - up to four times longer lifetime compared to standard lamps - and last up to 100,000 km (with an average annual mileage of 14,259 km and 60% light on). They are therefore ideal for frequent drivers.

Product datasheet

Technical data

Product information

Application (Category and Product specific)	Auxiliary lamp
---	----------------

General Product Information

Global order reference	64137ULT
------------------------	----------

Electrical Data

Power input	25 W ¹⁾
Nominal voltage	12.0 V
Nominal wattage	21 W
Test voltage	13.5 V

¹⁾ Maximum

Photometric Data

Nominal luminous flux	300 lm
Luminous flux tolerance	±17 %

Physical Attributes & Dimensions

Diameter	9 mm
Product weight	2.68 g
Length	38.9 mm
Lamp base	BAW9s

Lifetime Data

Lifespan B3	400 hr
Lifespan Tc	700 hr

Capabilities

Technology	AUX

Certificates & standards

ECE category	HY21W
Approval marks – approval	E1 approval

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)				
Date of declaration 09-07-2024				

Product datasheet

mary article identifier 4052899910256 4052899910744		
Candidate list substance 1	No declarable substances contained	
Declaration no. in SCIP database	In work	

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899910553	ULTRA LIFE HY21W		- x - x -	1.89 dm³	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.















