

ORIGINAL LINE

OEM quality for trucks



The cost-effective original spare parts for trucks

Continuously safe and robust: OSRAM ORIGINAL LINE is a balanced and economic solution for all standard requirements in the 24 V sector. Successfully used in millions of new vehicles from renowned manufacturers, whether as standard initial equipment or original spare parts. These reliable halogen lamps provide a convincing performance for standard requirements and are cost-effective. Convince yourself of the optimum price to performance ratio, the reliable OEM quality and the wide product range of the ORIGINAL LINE.

Product family datasheet

Technical data

Product description	Product information		Electrical data				Photometrical data
	Application (Category and Product specific)	Order reference	Power input	Nominal voltage	Nominal wattage	Test voltage	Luminous flux
ORIGINAL LINE H1	Halogen headlight lamp	64155	84 W ¹⁾	24.0 V	70.00 W	28.0 V	1900 lm
ORIGINAL LINE H2	Halogen headlight lamp	64175	84 W ¹⁾	24.0 V	70.00 W	28.0 V	2150 lm
ORIGINAL LINE H3	Halogen headlight lamp	64156	84 W ¹⁾	24.0 V	70.00 W	28.0 V	500 lm
ORIGINAL LINE H4	Halogen headlight lamp	64196	85 / 80 W ¹⁾	24.0 V	75/70 W	28.0 V	1900/1200 lm
ORIGINAL LINE H4	Halogen headlight lamp	94196	85 / 80 W ¹⁾	24.0 V	75/70 W	28.0 V	1900/1200 lm
ORIGINAL LINE H7	Halogen headlight lamp	64215	75 W ¹⁾	24.0 V	70.00 W	28.0 V	1750 lm
ORIGINAL LINE H15	Halogen headlight lamp	64177	73 / 24 W ¹⁾	24.0 V	60/20 W	28.0 V	300/1500 lm

Product description	Luminous flux tolerance	Dimensions & weight		Lifespan		Additional product data	Capabilities
		Length	Diameter	Lifespan B3	Lifespan Tc	Base (standard designation)	Technology
ORIGINAL LINE H1	±15 %	67.5 mm	8.5 mm	400 h	650 h	P14.5s	HAL
ORIGINAL LINE H2	±15 %	31.0 mm	9 mm	90 h	250 h	X511	HAL
ORIGINAL LINE H3	±15 %	44.0 mm	11.5 mm	400 h	650 h	PK22s	HAL
ORIGINAL LINE H4	±15 / ±15 %	82.0 mm	17.0 mm	170 / 350 h ²⁾	400 / 800 h ²⁾	P43t	HAL
ORIGINAL LINE H4	±15 / ±15 %	82.0 mm	16.0 mm	170 / 500 h ²⁾	400 / 1500 h ²⁾	P43t	HAL
ORIGINAL LINE H7	±10 %	59.0 mm	12.0 mm	220 h	500 h	PX26d	HAL
ORIGINAL LINE H15	±10 / ±10 %	79.0 mm	13.0 mm	200 / 1500 h	400 / 3000 h	PGJ23t-1	HAL

Product description	Certificates & standards
	ECE category
ORIGINAL LINE H1	H1
ORIGINAL LINE H2	H2
ORIGINAL LINE H3	H3
ORIGINAL LINE H4	H4
ORIGINAL LINE H4	H4
ORIGINAL LINE H7	H7
ORIGINAL LINE H15	H15






Product family datasheet

1) Maximum

2) Filament 1

Product family datasheet

Download Data

File	
	360 Degree Image ORIGINAL TRUCK H1 64155
	360 Degree Image ORIGINAL TRUCK H3 64156
	360 Degree Image ORIGINAL TRUCK H4 64196
	360 Degree Image ORIGINAL TRUCK H7 64215
	360 Degree Image ORIGINAL TRUCK H15 64177

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

