

ORIGINAL LINE H4

OEM quality for trucks



The cost-effective original spare parts for trucks

Continuously safe and robust: OSRAM ORIGINAL LINE is a balanced and economic solution for all standard requirements in the 24 V sector. Successfully used in millions of new vehicles from renowned manufacturers, whether as standard initial equipment or original spare parts. These reliable halogen lamps provide a convincing performance for standard requirements and are cost-effective. Convince yourself of the optimum price to performance ratio, the reliable OEM quality and the wide product range of the ORIGINAL LINE.



Product datasheet

Technical data

Product information

Application (Category and Product specific)	Halogen headlight lamp
---	------------------------

General Product Information

Global order reference	94196
------------------------	-------

Electrical Data

Power input	85 / 80 W ¹⁾
Nominal voltage	24.0 V
Nominal wattage	75 W
Test voltage	28.0 V

¹⁾ Maximum

Photometric Data

Nominal luminous flux	1900/1200 lm
Luminous flux tolerance	±15 / ±15 %

Physical Attributes & Dimensions

Lamp base	P43t
Length	82.0 mm
Diameter	16.0 mm
Product weight	25.60 g

Lifetime Data

Lifespan B3	170 / 500 hr ¹⁾
Lifespan Tc	400 / 1500 hr ¹⁾

¹⁾ Filament 1 / Filament 2

Capabilities

Technology	HAL
------------	-----

Certificates & standards

ECE category	H4
--------------	----

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of declaration	09-07-2024

Product datasheet

Primary article identifier	4050300250632 4050300250618
Candidate list substance 1	No declarable substances contained
Declaration no. in SCIP database	In work

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300250656	ORIGINAL LINE H4		- x - x -	19.40 dm ³	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



OSRAM