# **OSRAM**

# TRUCKSTAR PRO

## Brightest OSRAM truck light





Excellent brightness

More light allows to see farther and therefore react sooner



More than double the service life

Reduced downtime and fleet costs compared to standard lamps



Very high vibration resistance

Suitable for heavy duty applications





#### The most powerful halogen truck light from OSRAM

Discover TRUCKSTAR PRO signal lamps - the brightest truck light from OSRAM with excellent value for money. With up to 100% more light than standard lamps, extremely long life and very high vibration resistance these 24 volt lamps are ideal for professional drivers while reducing downtime and fleet costs. Thanks to the high vibration resistance, TRUCKSTAR PRO lamps are suitable even for heavy duty applications. Due to their impressive brightness and more than double the service life compared to standard lamps, the lamps improve your safety while driving on the road.

## Product family datasheet

#### Technical data

	Product information		Electrical data				
Product description	Order reference	Application (Category and Product specific)	Power input	Nominal voltage	Nominal wattage	Power input toleranc e	Test voltage
TRUCKSTAR PRO P21/5W	7537TSP	Auxiliary lamp	28 / 10 W	24.0 V	21/5 W	±6 / ±10 %	28.0 V
TRUCKSTAR PRO W5W	2845TSP	Auxiliary lamp	7 W	24.0 V	5.00 W	±10 %	28.0 V
TRUCKSTAR PRO PY21W	7510TSP	Auxiliary lamp	28 W	24.0 V	21.00 W	±6 %	28.0 V
TRUCKSTAR PRO R10W	5637TSP	Auxiliary lamp	12.5 W	24.0 V	10.00 W	±10 %	28.0 V
TRUCKSTAR PRO T4W	3930TSP	Auxiliary lamp	5 W	24.0 V	4.00 W	±10 %	28.0 V

	Photometrical data		Dimensions & weight		Lifespan		Additional product data
Product description	Luminous flux	Luminous flux tolerance	Length	Diameter	Lifespan B3	Lifespan Tc	Base (standard designation)
TRUCKSTAR PRO P21/5W	440/40 lm	±15 / ±20 %	52.5 mm	25.0 mm	100 / 1000 h	200 / 2000 h	BAY15d
TRUCKSTAR PRO W5W	50 lm	±20 %	26.8 mm	10.0 mm	1000 h	4000 h	W2.1x9.5d
TRUCKSTAR PRO PY21W	250 lm	±20 %	52.5 mm	25.0 mm	250 h	500 h	BAU15s
TRUCKSTAR PRO R10W	125 lm	±20 %	37.5 mm	16.0 mm	1000 h	2000 h	BA15s
TRUCKSTAR PRO T4W	35 lm	±20 %	27.4 mm	9 mm	550 h	1000 h	BA9s

	Capabilities	Certificates & standards	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Product description	Technology	ECE category	Date of Declaration	Primary Article Identifier
TRUCKSTAR PRO P21/5W	AUX	P21/5W	06-03-2024	4008321798138   4008321837318   4052899423695   4062172121132   4062172158480
TRUCKSTAR PRO W5W	AUX	W5W	06-03-2024	4008321798077   4008321842619   4052899560543   4062172158305
TRUCKSTAR PRO PY21W	AUX	PY21W	05-03-2024	4008321130969   4008321135193   4008321616111   4008321798169   4008321837257   4008321856944   4052899341333   4062172121095   4062172121231   4062172121217   4062172158428

## Product family datasheet

	Capabilities	Certificates & standards	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Product description	Technology	ECE category	Date of Declaration	Primary Article Identifier
TRUCKSTAR PRO R10W	AUX	R10W	05-03-2024	4008321135070   4008321795205   4008321821232   4062172158398
TRUCKSTAR PRO T4W	AUX	T4W	05-03-2024	4008321174055   4008321130846   4008321795106   4008321842589   4062172158336

Product description	Candidate List Substance 1	Declaration No. in SCIP database
TRUCKSTAR PRO P21/5W	No declarable substances contained	In work
TRUCKSTAR PRO W5W	No declarable substances contained	In work
TRUCKSTAR PRO PY21W	No declarable substances contained	In work
TRUCKSTAR PRO R10W	No declarable substances contained	In work
TRUCKSTAR PRO T4W	No declarable substances contained	In work

### Product family datasheet

### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### **Disclaimer**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.











