

# ORIGINAL - METAL BASE

Original spare part



## The cost-effective original spare parts for trucks

Discover OSRAM's ORIGINAL signal lamps with metal bases - high-quality original spare parts for 24 volt lamps. Due to the wide product range, the lamps can be used for different applications: as position and parking lights, indicator, brake, fog and reversing lights as well as number plate and side position lights.

## Product family datasheet

### Technical data

Product description	Product information		Electrical data				
	Application (Category and Product specific)	Order reference	Power input	Nominal voltage	Nominal wattage	Power input tolerance	Test voltage
ORIGINAL - METAL BASE 3797	Auxiliary lamp	3797	3 W	24.0 V	2.00 W	±15 %	28.0 V
ORIGINAL - METAL BASE H21W	Auxiliary lamp	64138	28 W	24.0 V	21.00 W	±5 %	28.0 V
ORIGINAL - METAL BASE P21/5W	Auxiliary lamp	7537	28 / 10 W	24.0 V	21/5 W	±6 / ±10 %	28.0 V
ORIGINAL - METAL BASE P21W	Auxiliary lamp	7511	28 W	24.0 V	21.00 W	±6 %	28.0 V
ORIGINAL - METAL BASE R10W	Auxiliary lamp	5637	12.5 W	24.0 V	10.00 W	±10 %	28.0 V
ORIGINAL - METAL BASE R5W	Auxiliary lamp	5626	7 W	24.0 V	5.00 W	±10 %	28.0 V
ORIGINAL - METAL BASE R5W	Auxiliary lamp	5627	7 W	24.0 V	5.00 W	±10 %	28.0 V
ORIGINAL - METAL BASE T4W	Auxiliary lamp	3930	5 W	24.0 V	4.00 W	±10 %	28.0 V
ORIGINAL - METAL BASE 7529	Auxiliary lamp	7529	15 W	24.0 V	15.00 W	±10 %	28.0 V

Product description	Photometrical data		Dimensions & weight		Lifespan		Additional product data
	Luminous flux	Luminous flux tolerance	Length	Diameter	Lifespan B3	Lifespan Tc	Base (standard designation)
ORIGINAL - METAL BASE 3797	17.5 lm	±30 %	23.9 mm	9 mm	1000 h	2000 h	BA9s
ORIGINAL - METAL BASE H21W	600 lm	±15 %	38.9 mm	9 mm	150 h	400 h	BAY9s
ORIGINAL - METAL BASE P21/5W	440/40 lm	±15 / ±20 %	52.5 mm	27.0 mm	65 / 600 h	600 / 1600 h	BAY15d
ORIGINAL - METAL BASE P21W	460 lm	±15 %	52.5 mm	26.5 mm	200 h	400 h	BA15s
ORIGINAL - METAL BASE R10W	125 lm	±20 %	37.5 mm	16.0 mm	400 h	800 h	BA15s
ORIGINAL - METAL BASE R5W	50 lm	±25 %	37.5 mm	16.0 mm	80 h	250 h	BA15d
ORIGINAL - METAL BASE R5W	50 lm	±20 %	37.5 mm	16.0 mm	500 h	1000 h	BA15s
ORIGINAL - METAL BASE T4W	35 lm	±20 %	27.4 mm	8.8 mm	550 h	1000 h	BA9s
ORIGINAL - METAL BASE 7529	210 lm	±25 %	46.5 mm	25.0 mm	100 h	300 h	BA15s

Product description	Capabilities	Certificates & standards
	Technology	ECE category
ORIGINAL - METAL BASE 3797	AUX	-
ORIGINAL - METAL BASE H21W	AUX	H21W
ORIGINAL - METAL BASE P21/5W	AUX	P21/5W
ORIGINAL - METAL BASE P21W	AUX	P21W
ORIGINAL - METAL BASE R10W	AUX	R10W
ORIGINAL - METAL BASE R5W	AUX	R5W
ORIGINAL - METAL BASE R5W	AUX	R5W
ORIGINAL - METAL BASE T4W	AUX	T4W
ORIGINAL - METAL BASE 7529	AUX	-

## Product family datasheet

### Application advice

For more detailed application information and graphics please see product datasheet.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

