Product family datasheet

XENARC ORIGINAL

Four-year guarantee

The original spare parts with four-year guarantee

XENARC ORIGINAL lamps impress with a wide product range and the reliable OEM quality. Successfully used in millions of new vehicles from renowned manufacturers, whether as standard initial equipment or original spare parts. With up to 4,500 Kelvin color temperature, their light is closer to natural daylight than conventional halogen light with 3,200 Kelvin – and is thus more pleasant for the eyes. Thanks to the impressive intensity of the light, the lamps provide better visibility on the road. The durable lamps function as original spare parts of your motorcycle lamps and convince with their long lifetime. OSRAM provides a 4-year-guarantee for XENARC ORIGINAL lamps. Please note: XENARC lamp change is recommended to be carried out by a professional.

© 2026, OSRAM GmbH. All rights reserved.

Technical data

	Electrical Data					Photometric Data
Product description	**Power input**	**Nominal voltage**	**Nominal wattage**	**Power input tolerance**	**Test voltage**	**Nominal luminous flux**
XENARC ORIGINAL D1S	35 W	85 V	35 W	±3 %	13.5 V	3200 lm
XENARC ORIGINAL D1R	35 W	85 V	35 W	±3 %	13.5 V	2800 lm
XENARC ORIGINAL D2S	35 W	85 V	35 W	±3 %	13.5 V	3200 lm
XENARC ORIGINAL D2R	35 W	85 V	35 W	±3 %	13.5 V	2800 lm
XENARC ORIGINAL D3S	35 W	42 V	35 W	±3 %	13.5 V	3200 lm
XENARC ORIGINAL D4S	35 W	42 V	35 W	±3 %	13.5 V	3200 lm
XENARC ORIGINAL D4R	35 W	42 V	35 W	±3 %	13.5 V	2800 lm
XENARC ORIGINAL D8S	25 W	42 V	25 W	±15 %	13.5 V	2000 lm

	Physical Attributes & Dimensions			Lifetime Data
Product description	**Lamp base**	**Length**	**Diameter**	**Lifespan B3**
XENARC ORIGINAL D1S	PK32d-2	83.2 mm	9 mm	2000 hr
XENARC ORIGINAL D1R	PK32d-3	83.2 mm	9 mm	2000 hr
XENARC ORIGINAL D2S	P32d-2	77.3 mm	9 mm	2000 hr
XENARC ORIGINAL D2R	P32d-3	77.3 mm	9 mm	2000 hr
XENARC ORIGINAL D3S	PK32d-5	83.2 mm	9 mm	2000 hr
XENARC ORIGINAL D4S	P32d-5	77.3 mm	9 mm	2000 hr
XENARC ORIGINAL D4R	P32d-6	77.3 mm	9 mm	2000 hr
XENARC ORIGINAL D8S	PK32d-1	83.2 mm	9 mm	2500 hr

		Certificates & standards	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Product description	**Lifespan Tc**	**ECE category**	**Primary article identifier**	**Candidate list substance 1**	**CAS No. of substance 1**
XENARC ORIGINAL D1S	3000 hr	D1S [1)]	4008321584816 | 4062172078702 | 4052899600423 | 4062172078726 | 4008321184276 | 4008321184474 | 4062172396806 | 4062172078689 | 4062172078740	Lead	7439-92-1
XENARC ORIGINAL D1R	3000 hr	D1R [1)]	4008321329318 | 4008321025265 | 4008321184498 | 4052899339828	Lead	7439-92-1

© 2026, OSRAM GmbH. All rights reserved.

Product family datasheet

		Certificates & standards	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Product description	**Lifespan Tc**	**ECE category**	**Primary article identifier**	**Candidate list substance 1**	**CAS No. of substance 1**
XENARC ORIGINAL D2S	3000 hr	D2S [1)]	4008321192882 | 4008321184573 | 4008321192868 | 4062172396745 | 4008321202062 | 4052899600447	No declarable substances contained	7439-92-1
XENARC ORIGINAL D2R	3000 hr	D2R [1)]	4008321192929 | 4008321192905 | 4008321184634	No declarable substances contained	7439-92-1
XENARC ORIGINAL D3S	4000 hr	D3S [1)]	4008321807649 | 4052899199569 | 4052899183650 | 4062172084574 | 4062172066754 | 4008321735201 | 4052899600485 | 4062172396837 | 4008321807663	Lead	7439-92-1
XENARC ORIGINAL D4S	4000 hr	D4S [1)]	4008321620132 | 4008321736765 | 4008321406958 | 4008321349392 | 4052899600508 | 4008321620118 | 4052899258389 | 4062172396776 | 4008321620095	No declarable substances contained	
XENARC ORIGINAL D4R	3000 hr	D4R [1)]	4008321349576 | 4008321736789	No declarable substances contained	
XENARC ORIGINAL D8S	4000 hr	D8S [1)]	4062172081153 | 4008321787019 | 4052899254756 | 4062172354103 | 4062172081092	Lead	7439-92-1

© 2026, OSRAM GmbH. All rights reserved.

Product description	Safe use instruction	Declaration no. in SCIP database
XENARC ORIGINAL D1S	The identification of the Candidate List substance is sufficient to allow safe use of the article.	854dcb23-d268-491f-ab0f-a5869c6f8c90 | 31336244-710b-47dc-bdf3-6d8e2c776b82 | a7f8360d-3aae-4fda-94ee-1571431ce2ad | 9aaef5e5-deb6-4a3c-8e15-eaa63c9f017b | 76b60f0a-2058-4902-a1ed-0486e0da9b7b | a9e37cbd-eb09-43c9-8f5e-6cc733f299b2 | 4c0fd8fc-8702-446b-9c40-bdc8ba72ff65 | 1fe48148-eada-4dcd-8441-4414d13a2b07 | d77cbbd7-7150-4270-8d80-8d074bdf807b | fd46009f-7d87-458a-a042-02761bfcff85 | e88095ba-ba24-47f9-a9e6-67cf6f88eeda
XENARC ORIGINAL D1R	The identification of the Candidate List substance is sufficient to allow safe use of the article.	33e2897b-c2cd-4c91-b5e4-834e11ec7de1 | b5fd4437-2cb2-4153-be83-0e76f5be8e7e | 57d74286-3c45-4bd7-8013-1e6bc20bbe81 | 9db2db3a-5cb5-42da-8d7a-a7310a40697a
XENARC ORIGINAL D2S		0e318d81-415f-4380-b08c-c047e93aa3de
XENARC ORIGINAL D2R		4d51eabc-c5f6-4368-8195-1b8229a19c39

© 2026, OSRAM GmbH. All rights reserved.

Product family datasheet

Product description	Safe use instruction	Declaration no. in SCIP database
XENARC ORIGINAL D3S	The identification of the Candidate List substance is sufficient to allow safe use of the article.	5aef8baf-bb8d-4ec6-948c-e2f16206841e | 61cedfc4-3556-4aaa-8669-7ecfed4d8666 | af212de5-b2c7-404c-acbe-c2ccabb83891 | 4ba45c38-8f60-4555-8439-6505375ae44e | 0a4d97a8-a9fd-4b6e-82eb-08e719745496 | 6ee45626-045c-415b-b12b-09cf7da79801 | b5de96fe-db0e-4cfb-9cd6-b43b44e32863 | d8af400e-6a40-4389-b185-d937af5eda3a | 376b0721-24ea-47fb-bfec-afe17d86ad60 | 6e275300-8ea9-4bd5-bf1a-aa729070f942 | 49060069-850f-4c78-a673-69f4a461d650 | 8b6f0291-a6c0-4867-8df0-c00e69eb2091
XENARC ORIGINAL D4S		No declarable substances contained
XENARC ORIGINAL D4R		No declarable substances contained
XENARC ORIGINAL D8S	The identification of the Candidate List substance is sufficient to allow safe use of the article.	4e12b30c-fca7-4555-9b48-d927cfeecea5 | 5514d2f4-519f-4db5-a8c1-cb1d19d694c1 | aeade777-d7aa-4866-b136-5177a71cc26a | 7f536438-e7cf-48ad-9756-27575fbc659b | 7ff303c4-87b9-4455-ae7a-6cb1e5924d63 | ef6fdca1-7f70-4231-892c-d0bfefe56436

[1] To be operated only with approved electronic control gear

© 2026, OSRAM GmbH. All rights reserved.

Download Data

	File
	User instruction GPRS_Safety symbols instructions
	Addon Technical Information Product Certificates HID
	ref_pim_amsp_product360degreeimages XENARC ORIGINAL D1S 66140
	ref_pim_amsp_product360degreeimages XENARC ORIGINAL D2S 66240
	ref_pim_amsp_product360degreeimages XENARC ORIGINAL D2R 66250
	ref_pim_amsp_product360degreeimages XENARC ORIGINAL D3S 66340
	ref_pim_amsp_product360degreeimages XENARC ORIGINAL D4S 66440
	ref_pim_amsp_product360degreeimages XENARC ORIGINAL D4R 66450
	ref_pim_amsp_product360degreeimages XENARC ORIGINAL D8S 66548 / XENARC COOL BLUE INTENSE D8S 66548CBN

Safety advice
XENARC lamp change is recommended to be carried out by a professional.

Application advice
For more detailed application information and graphics please see product datasheet.

Disclaimer
Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, OSRAM GmbH. All rights reserved.