Product family datasheet

# LEDriving PX-5

## LED daytime running light for retrofit

**LED pixel technology**
Dynamic appearance thanks to faceted optic and dotted pixel technology

**DRL**
LED daytime running light compatible with a wide range of car models and easy to install

**5200 K**
For drivers who want to increase visibility during the day

### Stylish highlights for your car

LEDriving PX-5 serves as a high performance and energy-efficient daytime running light for retrofitting on your vehicle. With its patterned diode design of five LEDs, the LEDriving PX-5 gives your vehicle a modern and stylish look. This daytime running light system is compatible with a wide range of vehicle models and is easy to install. The careful design of the LEDriving system ensures a horizontal tilt of 10 degrees. In addition, the left-hand and right-hand lamps can be switched, thus making installation uncomplicated. Furthermore, the high color temperature of 5,200 Kelvin and long life of up to 5,000 hours provide endless driving pleasure with LEDriving PX-5. OSRAM provides a 3-year guarantee for this product. Note: LEDriving PX-5 is certified according to ECE, SAE and CCC regulations (ECE E4 approval; ECE R87 approval).


© 2026, OSRAM GmbH. All rights reserved.

# Product family datasheet

## Technical data

| | Electrical Data | | Photometric Data | |
|---|---|---|---|---|
| **Product description** | **Nominal voltage** | **Nominal wattage** | **Color temperature** | **Nominal luminous flux** |
| LEDriving PX-5 | 12 V | 12 W | 5200 K | 300 lm |
| LEDriving PX-5 | 12 V | 12 W | 5200 K | 550 lm |

| | Physical Attributes & Dimensions | Additional product data | Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) | |
|---|---|---|---|---|
| **Product description** | **Length** | **Connector to lamp** | **Candidate list substance 1** | **CAS No. of substance 1** |
| LEDriving PX-5 | 160.0 mm | Wire Kit | Lead | 7439-92-1 |
| LEDriving PX-5 | 160.0 mm | Wire Kit | Lead | 7439-92-1 |

| Product description | Safe use instruction | Declaration no. in SCIP database |
|---|---|---|
| LEDriving PX-5 | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 24fd4b7d-c774-46f3-9b44-7c1767b813ea |
| LEDriving PX-5 | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 7a05b6d4-2aed-41c9-afdf-7da8dfd39471 |


© 2026, OSRAM GmbH. All rights reserved.

# Product family datasheet

## Download Data

| | File |
|---|---|
| | User instruction<br>LED Daytime Running Light Kit LEDDRL301 (User Manual) |
| | User instruction<br>LED Daytime Running Light Kit LEDDRL301 CL15 (User Manual) |
| | User instruction<br>GPRS_Safety symbols instructions |

**Legal advice**

ECE E4 approvalECE R87 approval

**References / Links**

Guarantee terms are available at www.osram.com/am-guarantee

**Application advice**

For more detailed application information and graphics please see product datasheet.

**Disclaimer**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.


© 2026, OSRAM GmbH. All rights reserved.