Product datasheet

LEDriving PX-5

LED daytime running light for retrofit



LED pixel technology
Dynamic appearance thanks to faceted optic and dotted pixel technology

DRL
LED daytime running light compatible with a wide range of car models and easy to install

5200 K
For drivers who want to increase visibility during the day



Stylish highlights for your car

LEDriving PX-5 serves as a high performance and energy-efficient daytime running light for retrofitting on your vehicle. With its patterned diode design of five LEDs, the LEDriving PX-5 gives your vehicle a modern and stylish look. This daytime running light system is compatible with a wide range of vehicle models and is easy to install. The careful design of the LEDriving system ensures a horizontal tilt of 10 degrees. In addition, the left-hand and right-hand lamps can be switched, thus making installation uncomplicated. Furthermore, the high color temperature of 5,200 Kelvin and long life of up to 5,000 hours provide endless driving pleasure with LEDriving PX-5. OSRAM provides a 3-year guarantee for this product. Note: LEDriving PX-5 is certified according to ECE, SAE and CCC regulations (ECE E4 approval; ECE R87 approval).

© 2024, OSRAM GmbH. All rights reserved.

Technical data

Product information

Order reference	LEDDRL301

Electrical data

Nominal voltage	13.2 V
Nominal wattage	12.5 W

Photometrical data

Color temperature	5200 K
Luminous flux	550 lm

Dimensions & weight

Length	160.0 mm
Product weight	552.00 g
Width	30.0 mm
Height	23.0 mm

Lifespan

Guarantee	3 years

Additional product data

Connector to lamp	Wire Kit

Capabilities

Technology	LED

Certificates & standards

Standards	ECE R87
Approval marks – approval	E4 approval

Country specific categorizations

Order reference	LEDDRL301

Logistical data

Commodity code	85122000900

Environmental information

© 2024, OSRAM GmbH. All rights reserved.

Product datasheet

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Date of Declaration	06-03-2024
Primary Article Identifier	4008321781215 | 4008321832382 | 4052899525498
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	7a05b6d4-2aed-41c9-afdf-7da8dfd39471

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321781215	LEDriving PX-5	Folding carton box 1	- x - x -		934.00 g
4052899089563	LEDriving PX-5	Shipping carton box 5	444 mm x 305 mm x 231 mm	31.28 dm^3	4349.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

	File
	User instruction 336028_LED Daytime Running Light Kit LEDDRL301 (User Manual)

Legal advice

ECE E4 approval

ECE R87 approval

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2024, OSRAM GmbH. All rights reserved.








OSRAM

© 2024, OSRAM GmbH. All rights reserved.