

产品系列数据表

FOG BREAKER

黄光提升高达200%



黄光提升高达**200%**
与标准灯相比，可提高能见度



亮度提升**60%**的光量
与标准卤素灯相比，具有更高能见度和
更短反应时间



可达**2,600 K**
日间行车照明让可见范围更宽广



为雾天、雨天和雪天提供更清晰的视野

黄光增亮高达200%且与标准品相比，亮度提升高达60%，FOG BREAKER 即使是在雨雪雾，沙尘暴等极端天气情况下也能提供良好的视野。这款产品不符合ECE标准。意味着它们不能被广泛使用。大范围运用有可能会被吊销营业执照或遭受保险损失。某些国家不允许销售和使用这些产品。请与当地的经销商联系，了解您国家的使用规则。

产品系列数据表

技术参数

产品描述	电参数				光度数据
	功率输入	标称电压	标称功率	测试电压	光通量
FOG BREAKER ≙ H1	68 W ¹⁾	12 V	55 W	13.2 V	1500 lm
FOG BREAKER ≙ H3	68 W ¹⁾	12 V	55 W	13.2 V	1550 lm
FOG BREAKER ≙ H4	75 / 68 W ¹⁾	12 V	60/55 W	13.2 V	1700/1100 lm
FOG BREAKER ≙ H7	58 W ¹⁾	12 V	55 W	13.2 V	1750 lm
FOG BREAKER ≙ H8	43 W ¹⁾	12 V	35 W	13.2 V	1350 lm
FOG BREAKER ≙ H11	62 W ¹⁾	12 V	55 W	13.2 V	1750 lm
FOG BREAKER ≙ H16	22.5 W ¹⁾	12 V	19 W	13.2 V	500 lm
FOG BREAKER ≙ HB3	73 W ¹⁾	12 V	60 W	13.2 V	1700 lm
FOG BREAKER ≙ HB4	62 W ¹⁾	12 V	51 W	13.2 V	1100 lm

产品描述	光通量容许偏差	Physical Attributes & Dimensions	寿命		认证与标准	Environmental & Regulatory Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
		直径	Lifespan B3	使用寿命 Tc	ECE 分类	Primary Article Identifier
FOG BREAKER ≙ H1	±15 %	8.5 mm	400 hr	650 hr		4052899039681 4052899932210
FOG BREAKER ≙ H3	±15 %	11.0 mm	400 hr	650 hr		4052899932227 4052899039704
FOG BREAKER ≙ H4	±15 %	17.0 mm	250 / 400 hr ²⁾	500 / 900 hr ²⁾		4052899932234 4052899039735
FOG BREAKER ≙ H7	±15 %	12.0 mm	330 hr	550 hr		4052899932203 4052899039766
FOG BREAKER ≙ H8	±15 %	11.7 mm	400 hr	800 hr		4052899503298 4052899233959
FOG BREAKER ≙ H11	±15 %	9.8 mm	350 hr	580 hr		4052899932241 4052899039780
FOG BREAKER ≙ H16	+10 %...15 %	9.5 mm				4052899280922
FOG BREAKER ≙ HB3	±12 %	12.0 mm	280 hr	550 hr		4052899047556 4052899932258 4052899047532
FOG BREAKER ≙ HB4	±15 %	12.0 mm	860 hr	1720 hr		4052899047570 4052899047594 4052899932265

产品描述	Candidate List Substance 1	Declaration No. in SCIP database
FOG BREAKER ≙ H1	No declarable substances contained	No declarable substances contained

产品系列数据表

产品描述	Candidate List Substance 1	Declaration No. in SCIP database
FOG BREAKER ≙ H3	No declarable substances contained	No declarable substances contained
FOG BREAKER ≙ H4	No declarable substances contained	No declarable substances contained
FOG BREAKER ≙ H7	No declarable substances contained	No declarable substances contained
FOG BREAKER ≙ H8	No declarable substances contained	No declarable substances contained
FOG BREAKER ≙ H11	No declarable substances contained	No declarable substances contained
FOG BREAKER ≙ H16	No declarable substances contained	No declarable substances contained
FOG BREAKER ≙ HB3	No declarable substances contained	No declarable substances contained
FOG BREAKER ≙ HB4	No declarable substances contained	No declarable substances contained

1) 最大

2) 灯丝1

产品系列数据表

下载数据

文件	
	User instruction GPRS_Safety symbols instructions
	Addon Technical Information Certificate overview OSRAM Argentina

法律建议

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

应用建议

更多详细应用信息和图形,请参阅产品数据表。

免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。

