

OPTOTRONIC Intelligent – DALI LT2

Compact constant current LED driver – Dimmable



Product family features

- Supply voltage: 220...240 V
- Line frequency: 0 Hz | 50 Hz | 60 Hz
- Line voltage: 198...264 V
- Safety according to EN 61347-1, 61347-2-3, 61347-2-13, 62384
- RI suppression: to EN 55015/CISPR 15
- Line harmonics according to EN 61000-3-2
- Immunity according to EN 61547
- Lifetime: up to 100,000 h
- Type of protection: IP20
- Independent connection via through-looping (except OTi DALI 15)

Product family benefits

- Versatile DALI window driver due to flexible output characteristic
- Very high efficiency
- Protection of the system thanks to thermal management and Smart Control
- High-quality dimming of 1...100 % by amplitude dimming

Versatile scope of application due to OSRAM DALI Technology:

- Easy to use in corridors and restrooms because of three-level Corridor function
- Touch DIM application: easy to control via pushbutton or sensor
- Energy efficient Touch DIM operation due to automatic switch-off at sufficient residual light
- Suitable for emergency Installations (acc. to EN 60598-2-22 and IEC 61347-2-13, appendix J) thanks to DC detection (0 Hz, pulsating DC), on/off switchable
- Feedback of power consumption and operating hours (Fit for SMART GRID)
- Suitable for buildings according to EPBD/BREEAM/LEED due to automatic Constant Lumen Output setting



Product family datasheet

Areas of application

- Installation in emergency lighting systems according to IEC 61347-2-13, appendix J
- Suitable for use in luminaires with flexible current setting (DALI, CLO, LEDset)
- Suitable for indoor SELV installations
- Suitable for luminaires of protection classes I and II
- Suitable for downlights, spotlights and LED panels
- Installation via Cable Clamp Kit possible (depending on version of product)

Product family datasheet

Technical data

Product description	Electrical data					
	Nominal input voltage	Mains frequency	Input voltage AC	Input voltage DC	Total harmonic distortion	Power factor λ
OTi DALI 15/220...240/1A0 LT2	220...240 V	0/50/60 Hz	198...264 V ¹⁾	176...276 V	< 10 % ²⁾	0.45C...0.95
OTi DALI 25/220...240/700 LT2	220...240 V	0/50/60 Hz	198...264 V ¹⁾	176...276 V	< 20 % ²⁾	0.49C...0.95
OTi DALI 35/220...240/1A0 LT2	220...240 V	0/50/60 Hz	198...264 V ¹⁾	176...276 V	< 20 %	0.72C...0.95
OTi DALI 50/220...240/1A4 LT2 FAN	220...240 V	0/50/60 Hz	198...264 V ¹⁾	176...276 V	< 10 % ²⁾	0.81C...0.97

Product description	Efficiency in full-load	Device power loss	Inrush current	Max. ECG no. on circuit breaker 10 A (B)	Max. ECG no. on circuit breaker 16 A (B)	Max. ECG no. on circuit breaker 25 A (B)
OTi DALI 15/220...240/1A0 LT2	88 % ³⁾	2.4 W	5 A ⁴⁾	82	130	-
OTi DALI 25/220...240/700 LT2	88 % ³⁾	4.5 W	< 20 A ¹⁹⁾	50	80	-
OTi DALI 35/220...240/1A0 LT2	89 % ³⁾	5.7 W	< 20 A ¹⁹⁾	35	55	-
OTi DALI 50/220...240/1A4 LT2 FAN	91 % ³⁾	7.5 W	30 A ²³⁾	12	20	-

Product description	Surge capability (L/N-Ground)	Surge capability (L-N)	Nominal output voltage	U-OUT (working voltage)	Nominal output current
OTi DALI 15/220...240/1A0 LT2	2 kV	1 kV	7.5...54 V ⁵⁾	60 V	150...1050 mA ⁶⁾
OTi DALI 25/220...240/700 LT2	2 kV	1 kV	12...54 V ⁵⁾	60 V	180...700 mA ²⁰⁾
OTi DALI 35/220...240/1A0 LT2	2 kV	1 kV	15...54 V ⁵⁾	60 V	350...1050 mA ²⁰⁾
OTi DALI 50/220...240/1A4 LT2 FAN	2 kV ²⁴⁾	1 kV	15...54 V ⁵⁾	60 V	600...1400 mA ⁶⁾

Product description	Output current LEDset open	Output current LEDset shorted	Default output current	Output current tolerance	Output ripple current (100 Hz)
OTi DALI 15/220...240/1A0 LT2	75 mA	350 mA	350 mA ⁷⁾	±3 %	< 2 % ⁸⁾
OTi DALI 25/220...240/700 LT2	90 mA	500 mA	500 mA ⁷⁾	±3 %	< 1 % ⁸⁾
OTi DALI 35/220...240/1A0 LT2	175 mA	700 mA	700 mA ⁷⁾	±3 %	< 2 % ⁸⁾
OTi DALI 50/220...240/1A4 LT2 FAN	300 mA	1050 mA	1050 mA ⁷⁾	±3 %	< 2 % ⁸⁾

Product description	Output PSTLM	Output SVM	Nominal output power	Maximum output power	Current set
OTi DALI 15/220...240/1A0 LT2	≤1	≤0.4	18 W ⁹⁾	18 W	DALI / LEDset2

Product family datasheet

Product description	Output PSTLM	Output SVM	Nominal output power	Maximum output power	Current set
OTi DALI 25/220...240/700 LT2	≤1	≤0.4	27 W ²¹⁾	27 W	DALI / LEDset2
OTi DALI 35/220...240/1A0 LT2	≤1	≤0.4	35 W ²²⁾	35 W	DALI / LEDset2
OTi DALI 50/220...240/1A4 LT2 FAN	≤1	≤0.4	55 W ²⁵⁾	55 W	DALI / LEDset2

Product description	Galvanic isolation primary/secondary	Power loss in stand-by mode	Galvanic isolation DALI/mains	Galvanic isolation DALI/output
OTi DALI 15/220...240/1A0 LT2	SELV	≤0.27 W	Basic	SELV
OTi DALI 25/220...240/700 LT2	SELV	<0.1 W	Basic	SELV
OTi DALI 35/220...240/1A0 LT2	SELV	<0.1 W	Basic	SELV
OTi DALI 50/220...240/1A4 LT2 FAN	SELV	<0.15 W	Basic	SELV

Product description	Networked standby power	Dimensions & weight			
		Product weight	Cable cross-section, input side	Cable cross-section, output side	Wire preparation length, input side
OTi DALI 15/220...240/1A0 LT2	≤0.27 W ³⁾	100.00 g	0.2...1.5 mm ² ¹⁰⁾	0.2...1.5 mm ² ¹⁰⁾	8.0...9.0 mm
OTi DALI 25/220...240/700 LT2	≤0.10 W ³⁾	149.00 g	0.2...1.5 mm ² ¹⁰⁾	0.2...1.5 mm ² ¹⁰⁾	8.0...9.0 mm
OTi DALI 35/220...240/1A0 LT2	≤0.10 W ³⁾	149.00 g	0.2...1.5 mm ² ¹⁰⁾	0.2...1.5 mm ² ¹⁰⁾	8.0...9.0 mm
OTi DALI 50/220...240/1A4 LT2 FAN	≤0.15 W ³⁾	180.00 g	0.2...1.5 mm ² ¹⁰⁾	0.2...1.5 mm ² ¹⁰⁾	8.0...9.0 mm

Product description	Wire preparation length, output side	Height	Width	Length	Mounting hole spacing, length
OTi DALI 15/220...240/1A0 LT2	8.0...9.0 mm	30.0 mm	53.0 mm	95.0 mm	
OTi DALI 25/220...240/700 LT2	8.0...9.0 mm	29.5 mm	67.0 mm	103.0 mm	94.0 mm
OTi DALI 35/220...240/1A0 LT2	8.0...9.0 mm	29.5 mm	67.0 mm	103.0 mm	94.0 mm
OTi DALI 50/220...240/1A4 LT2 FAN	8.0...9.0 mm	25.0 mm	75.0 mm	110.0 mm	99.0 mm

Product description	Mounting hole spacing, width	Colors & materials Casing material	Temperatures & operating conditions		
			Ambient temperature range	Maximum temperature at tc test point	Max.housing temperature in case of fault
OTi DALI 15/220...240/1A0 LT2		Plastic	-20...+50 °C	80 °C ¹¹⁾	100 °C
OTi DALI 25/220...240/700 LT2	58.0 mm	Plastic	-20...+50 °C	75 °C ¹¹⁾	110 °C

Product family datasheet

Product description	Mounting hole spacing, width	Colors & materials	Temperatures & operating conditions		
		Casing material	Ambient temperature range	Maximum temperature at tc test point	Max.housing temperature in case of fault
OTi DALI 35/220...240/1A0 LT2	58.0 mm	Plastic	-20...+50 °C	75 °C ¹¹⁾	110 °C
OTi DALI 50/220...240/1A4 LT2 FAN	64.0 mm	Plastic	-20...+50 °C	80 °C ¹¹⁾	110 °C

Product description	Temperature range at storage	Permitted rel. humidity during operation	Lifespan	Additional product data	
			ECG lifetime	Predecessor EAN	Successor EAN
OTi DALI 15/220...240/1A0 LT2	-25...85 °C	5...85 % ¹²⁾	50000 / 100000 h ¹³⁾	4052899324879	4062172143912
OTi DALI 25/220...240/700 LT2	-25...85 °C	5...85 % ¹²⁾	50000 / 100000 h ¹³⁾		
OTi DALI 35/220...240/1A0 LT2	-25...85 °C	5...85 % ¹²⁾	50000 / 100000 h ¹³⁾		
OTi DALI 50/220...240/1A4 LT2 FAN	-25...85 °C	5...85 % ¹²⁾	50000 / 100000 h ²⁶⁾		

Product description	Capabilities			
	Dimmable	Dimming interface	Dimming range	Dimming method
OTi DALI 15/220...240/1A0 LT2	Yes	DALI-2 / Touch DIM / Touch DIM Sensor	1...100 % ¹⁴⁾	Amplitude Modulation
OTi DALI 25/220...240/700 LT2	Yes	DALI-2 / Touch DIM / Touch DIM Sensor	1...100 % ¹⁴⁾	Amplitude Modulation
OTi DALI 35/220...240/1A0 LT2	Yes	DALI-2 / Touch DIM / Touch DIM Sensor	1...100 % ¹⁴⁾	Amplitude Modulation
OTi DALI 50/220...240/1A4 LT2 FAN	Yes	DALI-2 / Touch DIM / Touch DIM Sensor	1...100 % ¹⁴⁾	Amplitude Modulation

Product description	Constant lumen function	Overheating protection	Overload protection	Short-circuit protection
OTi DALI 15/220...240/1A0 LT2	Programmable	Automatic reversible	Automatic reversible	Automatic reversible
OTi DALI 25/220...240/700 LT2	Programmable	Automatic reversible	Automatic reversible	Automatic reversible
OTi DALI 35/220...240/1A0 LT2	Programmable	Automatic reversible	Automatic reversible	Automatic reversible
OTi DALI 50/220...240/1A4 LT2 FAN	Programmable	Automatic reversible	Automatic reversible	Automatic reversible

Product description	No-load proof	Intended for no-load operation	Max. cable length to lamp/LED module	Suitable for fixtures with prot. class
OTi DALI 15/220...240/1A0 LT2	Yes	No	2.0 m ¹⁵⁾	I / II
OTi DALI 25/220...240/700 LT2	Yes	No	2.0 m ¹⁵⁾	I / II

Product family datasheet

Product description	No-load proof	Intended for no-load operation	Max. cable length to lamp/LED module	Suitable for fixtures with prot. class
OTi DALI 35/220...240/1A0 LT2	Yes	No	2.0 m ¹⁵⁾	I / II
OTi DALI 50/220...240/1A4 LT2 FAN	Yes	No	2.0 m ¹⁵⁾	I / II

Product description	Suitable for emergency lighting	Type of connection, output side	DALI-2 Diagnostic Data	Number of channels
OTi DALI 15/220...240/1A0 LT2	Yes	Push terminal	Yes ¹⁶⁾	1
OTi DALI 25/220...240/700 LT2	Yes	Push terminal	Yes ¹⁶⁾	1
OTi DALI 35/220...240/1A0 LT2	Yes	Push terminal	Yes ¹⁶⁾	1
OTi DALI 50/220...240/1A4 LT2 FAN	Yes	Push terminal	Yes ¹⁶⁾	1

Product description	Suitable for through-wiring	Programming interface	DALI-2 Energy Data	Programming
				Tuner4TRONIC Field App
OTi DALI 15/220...240/1A0 LT2	No	DALI, LEDset	Yes ¹⁷⁾	No
OTi DALI 25/220...240/700 LT2	Yes with optional cable clamp	DALI, LEDset	Yes ¹⁷⁾	No
OTi DALI 35/220...240/1A0 LT2	Yes with optional cable clamp	DALI, LEDset	Yes ¹⁷⁾	No
OTi DALI 50/220...240/1A4 LT2 FAN	Yes with optional cable clamp	DALI, LEDset	Yes ¹⁷⁾	No

Product description	Programming device	Programmable features		
		Operating Current	Lamp Operating Time	Driver Guard
OTi DALI 15/220...240/1A0 LT2	DALI / LEDset	Yes	Yes	No
OTi DALI 25/220...240/700 LT2	DALI / LEDset	Yes	Yes	No
OTi DALI 35/220...240/1A0 LT2	DALI / LEDset	Yes	Yes	No
OTi DALI 50/220...240/1A4 LT2 FAN	DALI / LEDset	Yes	Yes	No

Product description	DALI Settings	Emergency Mode	DALI-2 Luminaire Data	Configuration Lock
OTi DALI 15/220...240/1A0 LT2	Yes	Yes	Yes ¹⁸⁾	No
OTi DALI 25/220...240/700 LT2	Yes	Yes	Yes ¹⁸⁾	No
OTi DALI 35/220...240/1A0 LT2	Yes	Yes	Yes ¹⁸⁾	No
OTi DALI 50/220...240/1A4 LT2 FAN	Yes	Yes	Yes ¹⁸⁾	No

Product description	Soft Switch Off	Dim to Dark	TouchDIM + Sensor	Corridor Functionality
OTi DALI 15/220...240/1A0 LT2	Yes	No	Yes	Yes
OTi DALI 25/220...240/700 LT2	Yes	No	Yes	Yes
OTi DALI 35/220...240/1A0 LT2	Yes	No	Yes	Yes
OTi DALI 50/220...240/1A4 LT2 FAN	Yes	No	Yes	Yes

Product family datasheet

Product description	OEM Key	Certificates & standards		
		Approval marks – approval	Standards	Protection class
OTi DALI 15/220...240/1A0 LT2	Yes	ENEC 10 / VDE / EMC / EL / CE	Acc. to EN 61347-1/Acc. to EN 61347-2-13/Acc. to EN 55015/Acc. to EN 61547/Acc. to EN 61000-3-2/Acc. to EN 62384	II
OTi DALI 25/220...240/700 LT2	Yes	ENEC 10 / VDE / EMC / EL / CE / DALI-2	Acc. to EN 61347-1/Acc. to EN 61347-2-13/Acc. to EN 55015/Acc. to EN 61547/Acc. to EN 61000-3-2/Acc. to EN 62384/Acc. to EN 62386/Acc. to IEC 62386-101:Ed2/Acc. to IEC 62386-102:Ed2/Acc. to IEC 62386-207:Ed1	II
OTi DALI 35/220...240/1A0 LT2	Yes	ENEC 10 / VDE / EMC / EL / CE / DALI-2	Acc. to EN 61347-1/Acc. to EN 61347-2-13/Acc. to EN 55015/Acc. to EN 61547/Acc. to EN 61000-3-2/Acc. to EN 62384/Acc. to EN 62386/Acc. to IEC 62386-101:Ed2/Acc. to IEC 62386-102:Ed2/Acc. to IEC 62386-207:Ed1	II
OTi DALI 50/220...240/1A4 LT2 FAN	Yes	ENEC 10 / VDE / EMC / EL / CE / DALI-2	Acc. to EN 61347-1/Acc. to EN 61347-2-13/Acc. to EN 55015/Acc. to EN 61547/Acc. to EN 61000-3-2/Acc. to EN 62384/Acc. to EN 62386/Acc. to IEC 62386-101:Ed2/Acc. to IEC 62386-102:Ed2/Acc. to IEC 62386-207:Ed1	II

Product description	Type of protection	Logistical data	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
		Commodity code	Date of Declaration	Primary Article Identifier
OTi DALI 15/220...240/1A0 LT2	IP20	850440829000	19-05-2023	4052899324879 4062172143912

Product family datasheet

Product description	Type of protection	Logistical data	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
		Commodity code	Date of Declaration	Primary Article Identifier
OTi DALI 25/220...240/700 LT2	IP20	850440839000	28-04-2023	4052899488144
OTi DALI 35/220...240/1A0 LT2	IP20	850440839000	12-05-2023	4052899488168
OTi DALI 50/220...240/1A4 LT2 FAN	IP20	850440839000	14-04-2023	4052899488182

Product description	Candidate List Substance 1	CAS No. of substance 1	Safe Use Instruction	Declaration No. in SCIP database
OTi DALI 15/220...240/1A0 LT2	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	08ca3009-16b1-4104-8382-194565783c1f 949efc19-1526-4a20-a69c-14887c9c16ef
OTi DALI 25/220...240/700 LT2	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	1ad50b70-9551-4f76-a1b1-fa78c11c8e24
OTi DALI 35/220...240/1A0 LT2	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	ef386587-888a-4ecb-97c0-d615a42f9032
OTi DALI 50/220...240/1A4 LT2 FAN	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	bb67ec73-9cf7-40a1-b713-ffb71366060b

1) Permitted voltage range

2) At full load, 220...240 V, 50 Hz / see graphs

3) at 230 V, 50 Hz

4) $t_{width} = 220 \mu s$ (measured at 50 % I_{peak})

5) Maximum 60 V

6) $\pm 5\%$

7) LEDset deactivated

8) Ripple average at 100 Hz

9) Partial load 3...18 W

10) Solid or flexible leads

11) Maximum at the T_c -point

12) Maximum 56 days/year at 85 %

13) $T_c = 75^\circ C$, 0.2% / 1,000 h failure rate

14) For maximum nominal output current


15) Output wires must be routed as close as possible to each other

16) Acc. DALI part 253


Product family datasheet

- 17) Acc. DALI part 252
- 18) Acc. DALI part 251
- 19) $t_{\text{width}} = 50 \mu\text{s}$ (measured at 50 % I_{peak})
- 20) $\pm 3\%$
- 21) Partial load 7...27 W
- 22) Partial load 15...35 W
- 23) $t_{\text{width}} = 200 \mu\text{s}$ (measured at 50 % I_{peak})
- 24) Functional Earth
- 25) Partial load 22...55 W
- 26) $T_c = 80^\circ\text{C}$, 0.2% / 1,000 h failure rate


Product family datasheet




OTI DALI15220-2401A0LT2 NFC UNV1 OSRAM




502047_OTi DALI 25220-240700 LT2




384437_OTi DALI 25220-240700 LT2



502048_OTi DALI 35220-2401A0 LT2



384426_OTi DALI 35220-2401A0 LT2



485749_OTi DALI 50220-2401A4 LT2FAN

Product family datasheet

















Application advice

For more detailed application information and graphics please see product datasheet.















Sales and Technical Support

Sales and Technical Support www.osram.com

Download Data

File	
	User instruction OPTOTRONIC LED Power Supply
	Certificates OTI DALI 15 LT2 EATON AM34566 210720
	Certificates OTI DALI 15 LT2 INOTEC AM34566 210720
	Certificates LED drivers EMC 40011668 300922
	Certificates OT ENEC 40038447 130722
	Certificates 664763_CB-Certificate-OTi DALI 15
	Declarations of conformity OTi DALI LT2 UK DoC 4281294 180221
	Declarations of conformity OTI DALI LT2 CE 3365628 200821
	CAD data 660729_OTi DALI 15 LT2 IGS 61119
	CAD data 660730_OTi DALI 15 LT2 CADPDF 61119
	CAD data 660731_OTi DALI 15 LT2 STEP 61119
	CAD data 673587_OT Cable Clamp F Style IGS 61119
	CAD data 673588_OT Cable Clamp F Style STEP 61119
	CAD data PDF 673589_OT Cable Clamp F Style CADPDF 61119
	User instruction OPTOTRONIC LED Power Supply
	Certificates OT EMC 40038827 300922

Product family datasheet

	Declarations of conformity EATON(CEAG)-Conformity declaration AB42877_OTi_DALI_25_220-240_700_LT2
	Declarations of conformity INOTEC- Conformity declaration AB42877_OTi_DALI_25_220-240_700_LT2
	CAD data 3-dim 491388_OTi_DALI_25_35_LT2_STEP_61119
	CAD data 3-dim 491391_OTi_DALI_25_35_LT2_IGS_61119
	CAD data PDF 491387_OTi_DALI_25_35_LT2_CADPDF_61119
	Declarations of conformity EATON(CEAG)-Conformity declaration AB42876_OTi_DALI_35_220-240_1A0_LT2
	Declarations of conformity INOTEC- Conformity declaration AB42876_OTi_DALI_35_220-240_1A0_LT2
	User instruction OPTOTRONIC LED Power Supply
	Certificates OTI DALI 50 LT2 FAN CB DE1 59836 040320
	Declarations of conformity EATON(CEAG)-Conformity declaration AB42878_OTi_DALI_50_220-240_1A4_LT2_FAN
	Declarations of conformity INOTEC- Conformity declaration AB42878_OTi_DALI_50_220-240_1A4_LT2_FAN
	CAD data 3-dim 491394_OTi_DALI_50_LT2_FAN_STEP_61119
	CAD data PDF 491393_OTi_DALI_50_LT2_FAN_CADPDF_61119
	CAD data PDF 491395_OTi_DALI_50_LT2_FAN_IGS_61119

Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Product family datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172143912	OTi DALI 15/220...240/1A0 LT2	Shipping carton box 20	284 mm x 207 mm x 96 mm	5.64 dm ³	2270.00 g
4052899488144	OTi DALI 25/220...240/700 LT2	Shipping carton box 20	357 mm x 222 mm x 96 mm	7.61 dm ³	3231.00 g
4052899488168	OTi DALI 35/220...240/1A0 LT2	Shipping carton box 20	357 mm x 222 mm x 96 mm	7.61 dm ³	3231.00 g
4052899488182	OTi DALI 50/220...240/1A4 LT2 FAN	Shipping carton box 20	389 mm x 234 mm x 72 mm	6.55 dm ³	4118.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Accessories Optional

Product description	Accessory name	Accessory code
OTi DALI 15/220...240/1A0 LT2	OT CABLE CLAMP F-STYLE	▶ 4052899325555
OTi DALI 25/220...240/700 LT2	OT CABLE CLAMP B-STYLE	▶ 4052899077881
OTi DALI 25/220...240/700 LT2	OT CABLE CLAMP B-STYLE TL	▶ 4052899948051
OTi DALI 35/220...240/1A0 LT2	OT CABLE CLAMP B-STYLE	▶ 4052899077881
OTi DALI 35/220...240/1A0 LT2	OT CABLE CLAMP B-STYLE TL	▶ 4052899948051
OTi DALI 50/220...240/1A4 LT2 FAN	OT CABLE CLAMP A-STYLE	▶ 4052899089570
OTi DALI 50/220...240/1A4 LT2 FAN	OT CABLE CLAMP A-STYLE TL	▶ 4052899325982

Data privacy

This OSRAM driver can be configured using the Tuner4TRONIC software. This requires registering on www.myosram.com and downloading the Tuner4TRONIC software from the Internet. The Tuner4TRONIC software enables users to access and view the operational data of a luminaire or driver via the corresponding programming interfaces. A password key (Config Lock) must be set up in the driver via the Tuner4TRONIC software in order to control which users can access and view operational data. Follow the instructions for password setup. To grant an external person or company rights to access or view operational data, you can assign password keys. In this case, however, you are responsible for ensuring that the third party concerned takes notice of the information described here. However, OSRAM can read out operating data from devices for maintenance and service purposes even when a password key has been assigned. In individual cases, OSRAM will also use its access rights in order to optimize or improve driver hardware and driver functions. In accordance with data privacy principles, any user of operating data (luminaire manufacturers, third parties with access rights) must ensure that personal data (e.g. name, address, location IDs) are only merged with the prior written consent of the person (end user) concerned. The respective user of the operating data is responsible for providing evidence of consent.

Product family datasheet

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.