

6.6 A Current Controlled Halogen - Reflector Lamps for Series Operation


应用领域


- 机场照明



产品特点


- Low maintenance costs due to long lamp life
- Reliable and consistent light output enhances visibility over the life of the lamp
- FAA approved in conjunction with many OEM fixtures
- Durable construction provides resistance to the effects of vibration
- Broad product portfolio for runway, taxiway, and approach lighting
- IR radiation provides guidance in low visibility conditions
- Flicker-free operation
- Ability to reduce light output when needed
- Mercury-free





Connector A, female

PK30d Connector A female



Connector B, female round

PK30d Connector B female round

产品系列数据表

技术参数

	电参数	寿命
产品描述	标称功率	Average Rated Life
64333 A 40-15	40 W	1500 hr
64333 B 40-15	40 W	1000 hr
64336 A 62-15	62 W	1500 hr
64337 A 45-15	45 W	1500 hr
64337 B 45-15	45 W	1500 hr
64339 A 105-10	105 W	1000 hr
64333 C 40-15	40 W	1500 hr
64337 A 48-15	48 W	1500 hr
64339 AC 105-10	105 W	1000 hr
64337 B 48-15	48 W	1500 hr
64337 C 48-15	48 W	1500 hr
64339 B 105-10	105 W	1000 hr
64339 C 105-10	105 W	1000 hr
64338 AC 48-10	48 W	1000 hr
64331 SP-A 30-10	30 W	1000 hr
-	48 W	2000 hr

产品系列数据表

安全建议

为避免人身伤害或财产损失，卤素灯只能在设计有合适结构（护罩、网格等）的合适灯具中操作，以确保在灯破裂时无零件/碎片崩出。还必须给出警告标志来指示这些灯会散发高热量。详细资讯可根据要求索要。

应用建议

更多详细应用信息和图形,请参阅产品数据表。

免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。