

6.6 A Current Controlled Halogen - Single End Lamps for Series Operation



应用领域

- 机场照明

产品特点

- Low maintenance costs due to long lamp life
- Reliable and consistent light output enhances visibility over the life of the lamp
- FAA approved in conjunction with many OEM fixtures
- Durable construction provides resistance to the effects of vibration
- Broad product portfolio for runway, taxiway, and approach lighting
- IR radiation provides guidance in low visibility conditions
- Flicker-free operation
- Ability to reduce light output when needed
- Mercury-free



产品系列数据表

技术参数

产品描述	General Product Information		电参数	寿命
	ANSI编码	LIF	标称功率	Average Rated Life
64322	EXL	-	30 W	1500 hr
64311	-	J1/59	36 W	1500 hr
64321	-	J1/57	45 W	1500 hr
64320	EXM	-	45 W	1500 hr
64346	-	J1/58	100 W	1200 hr
64386	-	J1/39	200 W	1500 hr
64350	EVV	-	110 W	1000 hr
58750	EZL	-	200 W	1300 hr
64354	EWR	-	150 W	1500 hr

产品系列数据表

安全建议

为避免人身伤害或财产损失，卤素灯只能在设计有合适结构（护罩、网格等）的合适灯具中操作，以确保在灯破裂时无零件/碎片崩出。还必须给出警告标志来指示这些灯会散发高热量。详细资讯可根据要求索要。

应用建议

更多详细应用信息和图形,请参阅产品数据表。

免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。