

Lok-it! Metal Halide



应用领域


- 演唱会照明
- 舞会及俱乐部
- 舞台及剧场
- 演播室，电视电影
- 建筑照明及灯光秀

产品特点


- Compact design and short arc gap allows for smaller and brighter fixtures
- Fast lamp replacement with one-touch rotate and lock base and socket design
- Robust design with eXtreme Seal (XS) technology, allowing up to 450°C at the pinch seal
- Consistent lumen output over the life of the lamp
- Improved ceramic base allows high voltage up to 35kV
- Higher luminous efficacy than conventional HID lamps provides higher fixture efficiency



产品系列数据表



Lok-it! HSD 300W/80/P28



LOK-IT! HTI 1500 W/60/P50

产品系列数据表

技术参数

产品描述	电参数		光度数据	
	标称功率	标称电压	光通量	色温
Lok-it! HSD 300 W/80/P28	300 W	95 V	20500 lm	8700 K
Lok-it! HTI 700 W/60/P28	700 W	64 V	50000 lm	6000 K
Lok-it! HTI 700 W/75/P28	700 W	68 V	50000 lm	6700 K
Lok-it! HTI 700 W/75/P50	700 W	100 V	50000 lm	7250 K
Lok-it! HTI 700 W/60/P50	700 W	59 V	49000 lm	5800 K
Lok-it! HTI 1500 W/60/P50	1500 W	100 V	130000 lm	6000 K
Lok-it! HTI 1500 W/60/P50 M3W	1500 W	100 V	130000 lm	6000 K
Lok-it! HTI 1600 W/60/P50	1600 W	83.3 V	140000 lm	6000 K
Lok-it! HTI 2000 W/60/P50	2000 W	107 V	165000 lm	6000 K
Lok-it! HTI 2000 W/75/P50	2000 W	100 V	155000 lm	7500 K

产品描述	寿命
	Average Rated Life
Lok-it! HSD 300 W/80/P28	2000 hr
Lok-it! HTI 700 W/60/P28	750 hr
Lok-it! HTI 700 W/75/P28	750 hr
Lok-it! HTI 700 W/75/P50	750 hr
Lok-it! HTI 700 W/60/P50	750 hr
Lok-it! HTI 1500 W/60/P50	750 hr
Lok-it! HTI 1500 W/60/P50 M3W	750 hr
Lok-it! HTI 1600 W/60/P50	750 hr
Lok-it! HTI 2000 W/60/P50	1000 hr
Lok-it! HTI 2000 W/75/P50	1000 hr

产品系列数据表

安全建议

由于Lok-it!灯在工作时亮度高、紫外线辐射高、内压高，所有它只能在专为此目的设计的密闭外壳内工作。必须使用合适滤光片来确保紫外线辐射降至接受水平。如果灯破裂，会释放水银。必须采取特定的安全措施。备有安全性和处理相关信息可供索取，也可以在照明灯宣传单或操作说明书中查找相应信息。

应用建议

更多详细应用信息和图形,请参阅产品数据表。

免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。