

Lok-it! Power Series (PS)



应用领域

- 演唱会照明
- 舞会及俱乐部
- 舞台及剧场
- 演播室，电视电影
- 建筑照明及灯光秀

产品特点

- Compact design and short arc gap allows for smaller and brighter fixtures
- Robust design with eXtreme Seal (XS) technology, allowing up to 450°C at the pinch seal
- Consistent lumen output over the life of the lamp
- Improved ceramic base allows high voltage up to 35kV
- Higher luminous efficacy than conventional HID lamps provides higher fixture efficiency
- Lamps designated as "Brilliant" offer exceptional color rendering with CRI as high as 95



产品系列数据表

技术参数

产品描述	电参数		光度数据	
	标称功率	标称电压	光通量	色温
Lok-it! 1000/PS	1000 W	85 V	85000 lm	6000 K
Lok-it! 1000/PS Brilliant	1000 W	85 V	82000 lm	6000 K
Lok-it! 1400/PS Brilliant	1400 W	95.5 V	118000 lm	6000 K
Lok-it! 1700/PS	1700 W	84.5 V	135000 lm	6000 K
Lok-it! 1800/PS Brilliant	1800 W	88 V	148000 lm	6000 K
Lok-it! 2000/PS Brilliant	2000 W	108 V	165000 lm	6000 K

产品描述	寿命
	Average Rated Life
Lok-it! 1000/PS	950 hr
Lok-it! 1000/PS Brilliant	750 hr
Lok-it! 1400/PS Brilliant	750 hr
Lok-it! 1700/PS	750 hr
Lok-it! 1800/PS Brilliant	750 hr
Lok-it! 2000/PS Brilliant	750 hr

产品系列数据表

安全建议

由于Lok-it!灯在工作时亮度高、紫外线辐射高、内压高，所有它只能在专为此目的设计的密闭外壳内工作。必须使用合适滤光片来确保紫外线辐射降至接受水平。如果灯破裂，会释放水银。必须采取特定的安全措施。备有安全性和处理相关信息可供索取，也可以在照明灯宣传单或操作说明书中查找相应信息。

应用建议

更多详细应用信息和图形,请参阅产品数据表。

免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。