

HMI DIGITAL



Druh použití


- not relevant
- Stage & Theatre
- Professional & High Speed Photography

Vlastnosti produktu


- Reduced flicker when used with high-speed electronic ballasts (up to 1000 Hz and higher)
- Suited for both analog and digital film productions
- High intensity light providing true color performance with a >90
- Capable of hot restrike ignition
- High stability of color temperature over lifetime
- Robust design provide durability during transport
- High energy efficiency providing up to 100 lm/W
- Enhanced safety with UV-Stop (UVS) feature on all DIGITAL types



Technický list řady výrobků



HMI 1600W Digital, product line drawing top neutral dimensions



HMI 1600W Digital, product line drawing top neutral dimensions

Technický list řady výrobků

Technické údaje

	Parametry			Fotometrické údaje
Popis výrobku	Jmenovitý výkon	Jmenovité napětí	Jmenovitý proud	Světelný tok
HMI DIGITAL 200 W	200 W	69 V	2.9 A	16000 lm
HMI DIGITAL 400 W	400 W	75 V	5.3 A	32500 lm
HMI DIGITAL 575 W	575 W	94 V	6.1 A	49000 lm
HMI DIGITAL 800 W	800 W	95 V	8.4 A	69000 lm
HMI DIGITAL 1200 W	1200 W	100 V	12 A	110000 lm
HMI DIGITAL 1600 W	1600 W	155 V	10.3 A	144000 lm
HMI DIGITAL 1800 W	1800 W	140 V	12.9 A	165000 lm
HMI DIGITAL 2500 W	2500 W	118 V	24.5 A	220000 lm
HMI DIGITAL 4000 W	4000 W	200 V	24 A	387000 lm
HMI DIGITAL 6000 W	6000 W	121 V	50 A	600000 lm
HMI DIGITAL 9000 W	9000 W	165 V	55 A	875000 lm
HMI DIGITAL 18000 W	18000 W	232 V	78 A	1600000 lm

	Životnost
Popis výrobku	Average Rated Life
HMI DIGITAL 200 W	200 hr
HMI DIGITAL 400 W	650 hr
HMI DIGITAL 575 W	1000 hr
HMI DIGITAL 800 W	1000 hr
HMI DIGITAL 1200 W	1000 hr
HMI DIGITAL 1600 W	750 hr
HMI DIGITAL 1800 W	750 hr
HMI DIGITAL 2500 W	500 hr
HMI DIGITAL 4000 W	500 hr
HMI DIGITAL 6000 W	500 hr
HMI DIGITAL 9000 W	400 hr
HMI DIGITAL 18000 W	350 hr

Technický list řady výrobků

Bezpečnostní pokyny

Because of their high luminance, UV radiation and high internal pressure during operation, HMI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Pokyny k použití

Podrobnější informace k použití a grafiku najdete v technickém listu.

Vyloučení odpovědnosti

Změny bez předchozího upozornění vyhrazeny. Chyby a opomenutí vyhrazeny. Vždy se ujistěte, že používáte nejnovější vydání.